

## OMNITRONIC UHF-204 Wireless Mic System 863-865MHz

Complete 4-channel UHF PLL microphone system

Réf. : 13063216

GTIN: 4026397478426



**L'article n'est plus disponible.**

### Caractéristiques:

- 4-channel receiver unit and 4 hand-held microphones with UHF PLL technology
  - Operation in the low-interference UHF band (863-865 MHz) with 4 fixed frequencies
  - 4 separate channels with volume controls and LEDs for power supply, carrier signal and audio signal
  - Balanced XLR output per channel
  - 6.3 mm jack for mixed signal output
  - Jack cable included
  - Microphones with mute switch and color caps for distinction on stage
  - Matching pocket transmitters can be ordered separately
  - Removable antennas (TNC connection)
  - Receiver unit in a rugged metal housing
  - Incl. mounting brackets for 483 mm rack installation
  - License-free and approved in the EU
  - Caractéristique directionnelle: Cardioïde
  - UHF 863-865 MHz sans inscription et sans frais en Europe
  - Boîtier du pupitre
  - (19") 48,3 cm installation en rack possible
- L'étendue des fournitures**
- 1 x microphone

### Logistique

EAN / GTIN: 4026397478426

Poids: 4,65 kg

Longueur: 0.53 m

Largeur: 0.29 m

Hauteur: 0.12 m

### Données techniques:

Type: Ensemble complet sans fil

Puissance totale de raccordement: 10,00 W

Type de micro:	Dynamique
Caractéristique directionnelle:	Cardioïde
Plage de fréquence:	40 - 18000 Hz
Bande de fréquences:	UHF 863-865 MHz
Sélection de la fréquence:	Fréquence fixe
Commutateur:	Commutateur muet; Commutateur marche/arrêt
Conception du boîtier:	Boîtier du pupitre (19") 48,3 cm installation en rack possible
Dimension:	Largeur : 42 cm Profondeur : 5 cm Hauteur : 22 cm
<b>Microphone</b>	
Batterie:	8 x Mignon (AA) (non incluse dans la livraison)
System:	Diversity, 4 channels
Carrier frequency:	863.010 MHz, 863.420 MHz, 864.300 MHz, 864.990 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
<b>Audio outputs:</b>	
Mic:	4 x XLR, bal.
Level/impedance:	400 mV, 2.2 kohms
Mic:	6.3 mm jack, unbal.
Level/impedance:	200 mV, 2.2 kohms
<b>Power supply</b>	
Receiver:	100-240 V AC, 50/60 Hz via supplied power unit
<b>Dimensions, weight</b>	
Receiver:	420 x 220 x 50 mm (L x W x H), 3 kg
Microphones:	50 x 265 mm (D x L), 280 g