



**L'article n'est plus disponible.**

### Caractéristiques:

#### FUTURELIGHT DMH-60 LED Moving Head

High performance LED Moving Head with 60 W LED

- 1 extra bright 60 W LED for best luminance
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- Automatic position correction
- PAN angle switchable between 630° and 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Sound-controlled via built-in microphone
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset

### Logistique

- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- DMX control via every standard DMX controller
- Commandé via Commande de la musique via Microphone; DMX; RDM
- Déjà préprogrammé pour %: Light`J

### ROADINGER Flightcase 2x DMH-30/DMH-40

PRO flightcase for 2 x FUTURELIGHT DMH-60/DMH-40/DMH-30 LED moving-head

- Developed for 51841836 FUTURELIGHT DMH-60 LED Moving Head, 51841835 FUTURELIGHT DMH-40 LED Moving Head, 51841825 FUTURELIGHT DMH-30 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- For perfect protection
- Roulettes
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

### EUROLITE Câble de sécurité AG-15 4 x 1000 mm 15 kg max.

Câble de sécurité de haute qualité

- Pour assurer des charges au-dessus des personnes
- Câble à torons ronds 6 x 19 avec insert en fibre
- Avec deux cosses
- Correspond DIN EN 12385-4:2008-06 et DIN 56927:2009-03
- Corde à cosse et raccord
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

#### L'étendue des fournitures

- 1 x rope, 1 x connecteur

### Données techniques:

---

#### FUTURELIGHT DMH-60 LED Moving Head

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	245 W
Mouvement de basculement max.TILT:	270° Positionnement
Mouvement de pivotement max. PAN:	630° Positionnement
Fréquence du flash:	1 - 13 Hz
Gobos:	Diamètre externe 27mm Diamètre de l'image 22mm
Canaux DMX:	14
Commande:	Commande de la musique via Microphone; DMX; RDM
Préprogrammé dans:	Light`J

Angle de départ (1/2 pic):	14°
Couleur:	Noir
Dimension:	Largeur : 30,1 cm Profondeur : 24,7 cm Hauteur : 40,6 cm
Poids:	11,40 kg
DMX channels:	14
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	13 Hz
LED type:	60 W, white
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	301 x 247 x 406 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

#### **ROADINGER Flightcase 2x DMH-30/DMH-40**

Charge maximale:	50 kg
Aide au transport:	Roulettes
Matériau:	Bois multiplex bouleau, 7 mm
Couleur:	Marron foncé, laminé
Dimension:	Largeur : 72,5 cm Profondeur : 40 cm Hauteur : 68 cm
Poids:	18,80 kg
Strength:	7 mm
Outside dimensions (W x D x H):	725 x 400 x 680 mm
Inside dimensions (W x D x H):	685 x 360 x 460 mm

#### **EUROLITE Collier de serrage TPC-10, argent**

Charge maximale BGV C1 (8 fois):	75 kg
Charge maximale WLL (4 fois):	150 kg
Diamètre du tuyau zone:	48 - 50 mm

Matériau:	Aluminium
Couleur:	Argenté
Vis de fixation:	M10
Dimension:	Longueur : 10 cm Largeur : 3 cm Profondeur : 9 cm
Poids:	160 g

**EUROLITE Câble de sécurité AG-15 4 x 1000 mm 15 kg max.**

Charge à protéger (BGV C1):	Max. 15 kg
Construction à base de câbles:	6 x 19 FC
Classe de résistance du câble:	1770
Norme:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Résistance à la rupture du câble:	1770 N/mm <sup>2</sup>
Surface des fils:	Galvanisé
Couleur:	Argenté
Plage de température:	-40° C - +100° C
Dimension:	Longueur : 1 m Diamètre : Ø 4 mm
Poids:	100 g
Poids de longueur:	0,0554 kg/m