



L'article n'est plus disponible.

Caractéristiques:

EUROLITE LED TMH-15 Moving Head Zoom Wash

Moving-head-wash 4-en-1 avec zoom et LED QCL 15 W

- Equipped with seven 15 W quadcolor LEDs with RGBW colors
- Compact lightweight
- Motorized zoom with 11°- 55° beam angle
- Color presets
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- L'appareil est refroidi par ventilateur
- Commandé via DMX; stand-alone
- Déjà préprogrammé pour %: Light'J; LED PC-Control 512
- Exempt de scintillements
- Avec un Angle de départ de 11° - 55°

Logistique

ROADINGER Flightcase 4x TMH-15 with wheels

PRO flightcase for 4 x TMH-15

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 chrome butterfly locks
- 4 chrome case handles
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- Roulettes
- Matériel de marque
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Poids: 44,60 kg

EUROLITE LED TMH-15 Moving Head Zoom Wash

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	130 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Refroidissement:	Ventilateur
Commande:	DMX; stand-alone
Préprogrammé dans:	Light'J; LED PC-Control 512
Projection:	Exempt de scintillements
Angle de départ:	11° - 55°
Angle de départ (1/2 pic):	11 - 28°
Angle de départ (1/10 pic):	25 - 55°
Puissance d'éclairage en lux (lx):	Étroit rouge (R) 3 m : 702 lx, 6 m : 182 lx Étroit vert (G) 3 m : 1131 lx, 6 m : 298 lx Étroit B bleu 3 m : 185 lx, 6 m : 50 lx Étroit blanc froid (CW) 3 m : 1139 lx, 6 m : 304 lx Étroit tous 3 m : 2272 lx, 6 m : 600 lx Large rouge (R) 3 m : 157 lx, 6 m : 42 lx Large vert (G) 3 m : 238 lx, 6 m : 65 lx Large B bleu 3 m : 54 lx, 6 m : 15 lx Large blanc froid (CW) 3 m : 329 lx, 6 m : 91 lx Large tous 3 m : 562 lx, 6 m : 155 lx
Couleur du boîtier:	Noir
Dimension:	Largeur : 25 cm Profondeur : 15 cm Hauteur : 33,5 cm

Poids:	5,35 kg
DMX channels:	13
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 15 W QCL
LED number:	7
Maximum PAN-movement:	630°
Maximum TILT-movement:	200°
Beam angle:	11° - 28°
Dimensions (L x W x H):	150 x 250 x 335 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

ROADINGER Flightcase 4x TMH-15 with wheels

Charge maximale:	100 kg
Aide au transport:	Roulettes
Utilisation de la marque:	Matériel de marque
Matériau:	Bois multiplex bouleau, 7 mm
Couleur:	Marron foncé, laminé
Dimension:	Largeur : 76 cm Profondeur : 61,5 cm Hauteur : 42 cm
Poids:	23,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	760 x 615 x 420 mm
Compartment dimensions (W x D x H):	125 x 280 x 300 mm
Accessory compartment (W x D x H):	100 x 610 x 320 mm