

# PSSO®

---

## Prime Set XL

Réf. : 20000514

GTIN:



**L'article n'est plus disponible.**

# PSSO®

---

## Prime Set XL

Réf. : 20000514

GTIN:

### Caractéristiques:

---

#### PSSO Système de haut-parleurs PRIME-212 club

Enceintes PA PRO, 2 x woofer 12", pavillon 1,5", 1 100 W RMS (Biamp)

- Rugged pro PA speaker, qualified for suspension and clubs
- Biamp operation
- Housing made of 18 mm (13 layers) and 25 mm (17 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.5"), 72 mm voice coil (2.8")
- Bassreflex system
- Neutrik Speakon connectors
- Scratch-resistant lacquer surface
- Applications: standing or suspended
- Pilote de CELTO ACOUSTIQUE
- Développé en Europe

### **PSSO Subwoofer PRIME-182 3000 W**

Subwoofer Bass Reflex PA PRO, woofer 2 x 18", 3 000 W RMS, 4 Ohm

- Rugged pro bassreflex subwoofer, qualified for clubs and touring applications
- Housing made of 25 mm (17 layers) and 18 mm (13 layers) birch plywood
- 2 x 45 cm (18") bass speaker, 115 mm voice coil (4.5"), diecast aluminum basket
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Parallel Neutrik Speakon connectors
- Metal flange for top speakers
- Carrying handles and rubber feet
- Scratch-resistant lacquer surface
- Pilote de CELTO ACOUSTIQUE
- Développé en Europe

### **PSSO Système d'amplificateur DSP PRIME**

Class D Amplificateur PA multicanal à alimentation à découpage, 4 x 400 W RMS (8 Ohm), 4 x 800 W RMS (4 Ohm)

- 6-channel PA amplifier with high-performance DSP, freely programmable
- Sample frequency: 96 kHz and 64-bit technology
- Premium components ensure excellent sound features