

---

**SOMMER CABLE DMX cable XLR 5pin 1m bk Hicon**

Câble de données de haute qualité

**Réf. : 3030746H**GTIN: 4049371168595

---

**L'article n'est plus disponible.****Description:**

---

DMX cable by premium manufacturer Sommer Cable

These premade cables are the perfect choice for the transmission of the 110 ohms AES/EBU DMX512 data format.

Important note: the use of a standard microphone cable is not recommended due to data and information losses (caused by the skin effect). In the lighting domain data losses cause a total jam with signal transmissions or the control of scanner systems.

The very affordable price of this cable should make it easy to switch from a standard microphone cable to a proper AES/EBU cable. Our AES/EBU cable guarantees the error-free data transfer even over longer distances of up to 100 metres. We use the BINARY 434 AES/EBU MKII AES/EBU cable with 100 % shielding and the HICON XLR connectors.

**Logistique**

---

EAN / GTIN: 4049371168595

Poids: 0,17 kg

Longueur: 0.20 m

Largeur: 0.24 m

Hauteur: 0.04 m

**Caractéristiques:**

---

- AES/EBU- and DMX-conformant, highly flexible
- Very good shielding through the use of copper spiral shielding and a fleece vaporized with aluminum
- Extremely robust with an especially strong jacket
- Only a little more expensive than a standard microphone cable
- For networking of scanners, lighting units, digital mixing boards, etc.
- For indoor and outdoor installation
- For connection of digital audio amplifiers, DAT-recorders, etc.
- HICON

## Données techniques:

---

Affectation des broches:	Pin 1 (GND) / Pin 2 (+) / Pin 3 (-) / Pin 4 (Data) / Pin 5 (Data)
Longueur du câble:	1 m
Raccord A:	1 x XLR (M) 5 broches
Raccord B:	1 x XLR (F) 5 broches
Utilisation de la marque:	HICON
Couleur:	Noir
Poids:	140 g

---