

## EUROLITE LED ML-56 COB 5600K 50W 60° bk

LED daylight spot in proven Multi Lens design

Réf. : 41604000

GTIN: 4026397440065



**L'article n'est plus disponible.**

### Caractéristiques:

- Equipped with one powerful 50 W COB LED
- Functions: dimmer, strobe effect, Master/Slave operation
- Operable in stand-alone mode or via DMX
- 1 or 3 DMX channels selectable for numerous applications
- Beam angle approximately 60°
- Different dimmer curves and dimmer speed adjustable
- 5600 K color temperature
- Mounting bracket for installations on a stand or a crossbeam
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via Control Board with LCD display and four operating buttons
- Ready for connection with power cord and safety plug
- With color filter frame
- Optional barndoors available
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Available in silver or black
- 1 LED puissante 50 W
- Commandé via stand-alone
- Déjà préprogrammé pour %: LED PC-Control 512

### Logistique

EAN / GTIN: 4026397440065

Poids: 4,40 kg

Longueur: 0.28 m

Largeur: 0.27 m

Hauteur: 0.38 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 85,00 W

Type de protection:	IP20
Type de lampe:	Lampe LED
LED:	1 x 50 W
Commande:	Stand-alone
Préprogrammé dans:	LED PC-Control 512
Angle de départ (1/2 pic):	60°
Couleur du boîtier:	Noir
Dimension:	Largeur : 30 cm Profondeur : 30 cm Hauteur : 24 cm
Poids:	3,90 kg
DMX channels:	1/3
DMX connection:	3-pin XLR
LED type:	Array 50 W
LED number:	1
Color temperature:	5600 K
Beam angle:	60°
Dimensions (L x W x H):	240 x 300 x 300 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle