


EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

Réf. : 41606200

GTIN: 4026397459838



Caractéristiques:

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Commandé via stand-alone; DMX; commande de la musique via microphone
- Avec un Angle de départ de 60°

Logistique

EAN / GTIN: 4026397459838

Poids: 9,20 kg

Longueur: 0.43 m

Largeur: 0.41 m

Hauteur: 0.26 m

Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 275 W

Type de lampe: Lampe LED

Fréquence du flash: 1 - 20 Hz

Canaux DMX: 3; 16; 19

Commande:	Stand-alone; DMX; commande de la musique via microphone
Fixtures disponibles pour:	LED PC-Control 512; Light Captain
Angle de départ (1/2 pic):	60°
Température de couleur:	3200K
Couleur du boîtier:	Noir
Dimension:	Largeur : 31,5 cm Profondeur : 34,5 cm Hauteur : 34,5 cm
Poids:	8,20 kg
DMX channels:	3/16/19
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED number:	16
LED type:	Array 20 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (W x D x H):	345 x 315 x 345 mm
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

Contenu de la livraison:
