

EUROLITE Audience Blinder 4xPAR-36 TCL LED bk

LED Audience Blinder with PAR-36 Blinder housing

Réf. : 42103477

GTIN: 4026397427677



L'article n'est plus disponible.

Caractéristiques:

- Equipped with 24 x 3 W TCLs (tricolor LEDs) distributed in 4 segments
- Each segment can be controlled individually via DMX
- Sound-control via built-in microphone; sensitivity adjustable
- Functions: static colors; automatic color change, 14 built-in programs and strobe effect with variable speed; Master/Slave
- 3, 5, 6, 9, 12, 15 DMX channels selectable for various applications
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Addressing via control panel with LC display
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- DMX control via every standard DMX controller
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains

Logistique

EAN / GTIN: 4026397427677

Poids: 10,20 kg

Longueur: 0.62 m

Largeur: 0.51 m

Hauteur: 0.24 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 175 W

Type de protection: IP20

Fréquence du flash: 1 - 20 Hz

Canaux DMX:	3
Angle de départ (1/2 pic):	16°
Dimension:	Largeur : 44,5 cm Profondeur : 15 cm Hauteur : 52,5 cm
Poids:	8 kg
DMX channels:	3/5/6/9/12/15
DMX connection:	3-pin XLR
Flash-rate:	20 Hz
LED type:	3 W TCL
LED number:	24
Beam angle:	16°
Dimensions (L x W x H):	150 x 445 x 525 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle