

EUROLITE LED KLS-801 Compact Light Set

Bar avec 4 spots équipés chacun de 7 LED 3 W 3-en-1 (RGB) et sac de transport

Réf. : 42109851

GTIN: 4026397420272



L'article n'est plus disponible.

Caractéristiques:

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 LED puissantes 3 W high-power 3in1 TCL RGB (mélange de couleurs homogène)-BR> spots pouvant être commandés individuellement
- Commandé via stand-alone; DMX; Pédale de commande câblée (facultatif); Commande de la musique via Microphone

Logistique

EAN / GTIN: 4026397420272

Poids: 13,10 kg

Longueur: 1.26 m

Largeur: 0.13 m

Hauteur: 0.40 m

Article encombrant

- Déjà préprogrammé pour %: Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Avec un Angle de départ de 30°
- Pivot TV
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

L'étendue des fournitures

- 1 x projecteur, 1 x sac

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	90,00 W
Type de protection:	IP20
Branchement électrique:	Alimentation électrique via Appareils froids (M) version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Sortie de courant:	4 x Appareils froids (F) version encastrable sécurisé 1 x Appareils froids (F) version encastrable Bypass
Type de lampe:	Lampe LED
LED:	7 x 3 W high-power 3in1 TCL RGB (mélange de couleurs homogène)
Canaux DMX:	15
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Commande:	Stand-alone; DMX; Pédale de commande câblée (facultatif); Commande de la musique via Microphone
Préprogrammé dans:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Angle de départ:	30°
Angle de départ (1/2 pic):	30°
Couleur du boîtier:	Noir
Système d'enregistrement:	Broche TV Ø 28 mm
Poids:	11,75 kg
Projecteur	
Dimension:	Largeur : 1,2 m Profondeur : 6,5 cm Hauteur : 31,5 cm
Sac	
Dimension:	Largeur : 1,25 m Profondeur : 12 cm Hauteur : 38 cm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle