

EUROLITE Moteur couple MD-2010 sécurisé

Moteur de boule à facettes pour boules jusqu'à 50 cm

Réf. : 50301500

GTIN: 4026397333152



Prix de catalogue: 47.48 €

TVA 19% incl.

Description:

This solid mirror ball motor can carry a load of up to 10 kg. This equals a mirror ball of approximately 50 cm, 12-fold safety margin included. The motor has a speed of 1 RPM (rotations per minute). This creates a peaceful effect, especially when you choose for a pin spot to shine on the mirror ball.

The motor is equipped with a patented mechanical drop protection against unintentional loosening of the axis as well as the required second eyelet for the attachment of the safety chain.

All Eurolite safety motors comply with the safety norm DIN EN ISO 12100 and relevant accident prevention regulations. Each production charge is subject to strict quality control which makes the motor suitable for discotheques and other public events. The MD-2010 is delivered with open wires that allow you to mount a fitting plug yourself.

Caractéristiques:

- La capacité de charge maximale se réfère toujours au poids réel de la boule à facettes, chaînes et matériel de fixation inclus
- 2 chaînes et 4 connecteurs rapides doivent être commandés séparément
- 1 tour par minute
- Le moteur doit toujours être installé avec une deuxième suspension indépendante
- Avant la première mise en service, le dispositif doit être contrôlé par un expert
- Adapté à une boule à facettes d'un diamètre de 50 cm max.
- Pour des domaines d'application tels que: Clubs/Écoles de danse
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

L'étendue des fournitures

- 1 x moteur, 1 x mode d'emploi

Logistique

EAN / GTIN: 4026397333152

Poids: 1,04 kg

Longueur: 0.20 m

Largeur: 0.20 m

Hauteur: 0.14 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	3,5 W
Type de protection:	IP20
Classe de protection:	SK I
Branchement électrique:	Fixe Câble de connexion aux extrémités de câble ouvertes
Conception du câble:	3 x 0,75 mm ² H05VV-F
Longueur du câble:	Env. 0,9 m
Vitesse de rotation:	1 tr/min , 360 ° avant/arrière
Charge maximale:	10 kg
Diamètre max. de la boule à facettes:	50 cm (EUROLITE)
Couleur du boîtier:	Noir mat
Diamètre des trous de fixation:	4 x Ø5mm; 2 x Ø10mm
Matériau:	Métal
Dimension:	Hauteur : 13 cm Diamètre : Ø 19 cm
Poids:	960 g