

LASERWORLD DS-1000RGB ShowNET (2021)

Laser de spectacle à diodes, interface réseau ShowNET et logiciel gratuit

Réf. : 51743280

GTIN: 4026397713503



L'article n'est plus disponible.

Caractéristiques:

- Suitable for both beginners and professional users
- Upgrades of version 2021: new back plate with Interlock IN and THRU, Power IN and THRU, new push buttons for X/Y Invert and the other functions, revised key switch, faster galvos (40 kpps @8° ILDA) and 50° maximum deflection
- Multiple preset laser patterns included
- Integrated Scan Fail Safety
- Low-maintenance due to Sealed Housing Technology
- 1000 mW guaranteed power
- Graphics capable - 40 kpps@8° ILDA
- Max scan angle 45°
- Full colour mixing - analog modulation
- Extremely sharp intense beams - 4mm beam diameter and low divergence of 1.1mrad
- Save safety settings direct to the laser and they apply in all modes
- Link multiple units with linking Power, DMX and ILDA
- Integrated ShowNET network interface with free laser control software included
- Start with your own professional laser show thanks to the intuitive Showeditor laser show software
- The Showcontroller software is supported as well and can be purchased additionally
- The integrated ShowNET allows for direct input through ILDA and LAN. Besides DMX, it is possible to trigger single frames via ArtNET. Custom frames and shows can be played back from an integrated SD card (included in delivery) - even in sound-to-light and stand-alone mode.
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; ILDA; Commande de la musique via Microphone; ArtNet

Logistique

EAN / GTIN: 4026397713503

Poids: 4,60 kg

Longueur: 0.35 m

Largeur: 0.29 m

Hauteur: 0.18 m

L'étendue des fournitures

- 1 x appareil, 1 x mode d'emploi, 1 x câble secteur/câble d'alimentation, 1 x clé, 1 x clé Allen, 1 x interlock, 1 x sac

Données techniques:

| | |
|-----------------------------------|---|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 40 W |
| Type de protection: | IP20 |
| Branchement électrique: | Alimentation électrique via P-Con (bleu), version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison) |
| Sortie de courant: | 1 x P-Con (gris), version encastrable |
| Classe laser: | 4 |
| Couleur du laser: | R/G/B |
| Module laser: | Rouge (R) 180 mW 638 nm Vert (G) 120 mW 520 nm B bleu 700 mW 450 nm |
| Refroidissement: | Refroidissement par convection passive |
| Commande: | Stand-alone; DMX; ILDA; Commande de la musique via Microphone; ArtNet |
| Couleur du boîtier: | Noir |
| Dimension: | Largeur : 14 cm Profondeur : 20 cm Hauteur : 11 cm |
| Poids: | 3,93 kg |