

EUROLITE LED TMH-61 Hypno Moving Head Beam

Beam avec 4 anneaux Hypno et LED COB 60 W en couleurs RGBW

Réf. : 51785896

GTIN: 4026397592924



L'article n'est plus disponible.

Caractéristiques:

- Beam effect with a 60 W COB LED in RGBW colors and 4 hypno rings with altogether 88 RGB SMD LEDs
- Compact lightweight
- 12, 27 or 29 DMX channels selectable
- Stepless RGBW color mixture, color presets and color change
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Internal programs
- LED hypno rings with stepless RGB color mixture - each color and each ring can be controlled individually, color presets and color changes
- Automatic position correction
- Positioning within 630° PAN and 210° TILT
- PAN-angle switchable between 630° and 540°
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone, sensitivity adjustable
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- DMX512 control via every standard DMX controller
- Effet beam
- L'appareil est refroidi par ventilateur
- Commandé via stand-alone; DMX
- Déjà préprogrammé pour %: Light 'J; LED PC-Control 512; Light Captain
- Exempt de scintillements

Logistique

EAN / GTIN: 4026397592924

Poids: 6,25 kg

Longueur: 0.44 m

Largeur: 0.28 m

Hauteur: 0.35 m

- Avec un Angle de départ de 2,5°

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	80 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Refroidissement:	Ventilateur
Commande:	Stand-alone; DMX
Préprogrammé dans:	Light'J; LED PC-Control 512; Light Captain
Projection:	Exempt de scintillements
Angle de départ:	2,5°
Angle de départ (1/2 pic):	2,5°
Couleur du boîtier:	Noir
Dimension:	Largeur : 24,5 cm Profondeur : 16,5 cm Hauteur : 35 cm
Poids:	5,40 kg
DMX channels:	12/27/29
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	25 Hz
LED number:	1 x COB + 88 x SMD
LED type:	60 W COB, RGBW + RGB SMD
Maximum PAN-movement:	630°
Maximum TILT-movement:	210°
Dimensions (L x W x H):	165 x 245 x 350 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle