

FUTURELIGHT PHS-265 WDMX incl. bulb

Versatile Moving Head

Réf. : 51838205

GTIN: 4026397235272



L'article n'est plus disponible.

Description:

Brakes the cable-chains!

As can be seen by its name, this PHS is akin to the 260E. In deed, it really is equipped with the same sharp and precise illustration and all the other highly developed features, such as the number of gobo wheels or the rotating 3-facet prism are identical, as well. The singularity of the PHS-265 WMDMX lies in its attached wireless DMX receiver. Always an advantage when mounting and remounting is continually needed. Annoying spaghetti syndromes will not occur again so you can save time and trouble with a truly powerful moving head.

Caractéristiques:

- With integrated wireless receiver for W-DMX operation
- Color-wheel with 7 different dichroic color filters, UV-filter plus white
- Slot-in gobo-system for exchanging gobos without tools
- Gobo-wheel with 7 static metal gobos plus open
- Gobo-wheel with 7 rotating gobos plus open
- With gobo-shake function
- Macro-function for rotating gobos/rotating prism combinations
- Motorized multistep-zoom (14°, 17°, 20°)
- Motorized focus
- Strobe effect with 1-13 flashes per second
- Rotating 3-facet prism
- Stepless frost-filter for fading the projections in or out
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off

Logistique

EAN / GTIN: 4026397235272

Poids: 29,85 kg

Longueur: 0.60 m

Largeur: 0.47 m

Hauteur: 0.51 m

- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Lamp already installed and adjusted from factory
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Power consumption:	485 W
DMX channels:	15
DMX connection:	3-pin XLR
Flash-rate:	13 Hz
Color-wheel:	7 dichroic filters, UV-filter plus open
Static gobo-wheel:	7 gobos and open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	23 mm
Maximum PAN-movement 630°:	in 2.5 s
Maximum TILT-movement 265°:	in 1.5 s
Length of base:	370 mm
Width of yoke:	420 mm
Height (head horizontal):	470 mm
Weight:	24 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle