

FUTURELIGHT PLB-130.i Beam Moving Head

High performance beam with Osram Sirius HRI 132 W lamp and unlimited PAN and TILT movement

Réf. : 51838946

GTIN: 4026397514773



L'article n'est plus disponible.

Caractéristiques:

- Supports RDM (Remote Device Management)
- High PAN/TILT speed and Infinity function (.i) for unlimited PAN and TILT movement
- 10, 12, 13 or 15 DMX channels selectable
- Parallel beam
- Color wheel with 14 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Effect wheel with rotating 8-facet prism
- The prism rotate in both directions and at different speeds
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction,
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- With Osram Sirius HRI 132 W lamp

Logistique

EAN / GTIN: 4026397514773

Poids: 11,80 kg

Longueur: 0.59 m

Largeur: 0.38 m

Hauteur: 0.27 m

- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After 8 devices the fixtures must have a renewed connection with the power mains
- DMX-control via any standard DMX-controller
- Déjà préprogrammé pour %: LED PC-Control 512

Données techniques:

| | |
|-----------------------------------|--|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 175,00 W |
| Préprogrammé dans: | LED PC-Control 512 |
| Dimension: | Largeur : 29,9 cm Profondeur : 39,8 cm Hauteur : 23,4 cm |
| DMX channels: | 10/12/13/15 |
| DMX connection: | 5-pin XLR |
| Sound-control: | via built-in microphone |
| Flash-rate: | 20 Hz |
| Color-wheel: | 14 dichroic filters plus open |
| Static gobo wheel: | 17 gobos and open |
| Maximum PAN-movement: | unlimited |
| Maximum TILT-movement: | unlimited |
| Beam angle: | 3° |
| Dimensions (L x W x H): | 234 x 299 x 398 mm |
| Weight: | 8.5 kg |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |