

FUTURELIGHT PSX-575 Scan

PRO scanner with multi-step zoom

Réf. : 51839975

GTIN: 4026397194838



L'article n'est plus disponible.

Caractéristiques:

- 8 brilliant dichroic colors plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in gobo system for exchanging gobos without tools
- Gobo wheel 1 with 6 rotating gobos plus open
- All gobos can be interchanged
- Gobo wheel 2 with 7 static metal gobos plus open
- With gobo shake function
- Effect wheel with rotating 3-facet prism
- Stepless frost filter for fading the projections in or out
- Macro function for rotating gobos/rotating prism combinations
- Motorized focus
- Motorized multistep zoom (18°, 20°, 22°)
- Steplessly adjustable iris
- Strobe effect with 1-13 flashes per second via shutter
- Mechanic dimmer
- Exact positioning via 16-bit Pan/Tilt movement resolution
- Control board with 4-digit display and foil keyboard for adjusting the DMX starting address, Pan/Tilt Reverse, Program, Reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone

Logistique

EAN / GTIN: 4026397194838

Poids: 32,60 kg

Longueur: 0.92 m

Largeur: 0.48 m

Hauteur: 0.43 m

Article encombrant

- For extremely bright MSR 575/2 lamp
- DMX control via every standard DMX controller
- Roue de gobo à gobos rotatifs
- Roue de gobo à gobos rotatifs, 6 gobos et ouvert
Gobos interchangeable
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	950 W
Mouvement de basculement max. TILT:	50° Positionnement
Mouvement de pivotement max. PAN:	180° Positionnement
Fréquence du flash:	1 - 13 Hz
Équipement:	Roue de gobo à gobos rotatifs
Gobos:	Roue de gobo à gobos rotatifs, 6 gobos et ouvert Diamètre externe 27mm Diamètre de l'image 23mm Gobos interchangeable
Canaux DMX:	16
Dimension:	Largeur : 39,5 cm Profondeur : 35 cm Hauteur : 80 cm
Poids:	28,20 kg
DMX channels:	16
DMX connection:	3-pin XLR
Flash-rate:	13 Hz
Color-wheel:	8 dichroic filters and open
Static gobo-wheel:	7 gobos and open
Rotating gobo-wheel:	6 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	23 mm
Maximum PAN-movement 180°:	in 0.85 s
Maximum TILT-movement 50°:	in 0.83 s
Dimensions (L x W x H):	800 x 395 x 350 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle