

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

Moving-head-beam 4-en-1 avec LED 15 W

Réf. : 51841305

GTIN: 4026397474091



Caractéristiques:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 14, 16 or 22 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device

Logistique

EAN / GTIN: 4026397474091

Poids: 7,50 kg

Longueur: 0.41 m

Largeur: 0.32 m

Hauteur: 0.27 m

- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	100,00 W
Dimension:	Largeur : 17,9 cm Profondeur : 35 cm Hauteur : 24,4 cm
DMX channels:	14/16/22
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED number:	7
LED type:	15 W QCL
Beam angle:	7°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 179 x 350 mm
Weight:	6 kg
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

Contenu de la livraison:
