

FUTURELIGHT EYE-15 RGBW Zoom LED Moving-Head Wash

Moving-head-wash 4-en-1 avec zoom

Réf. : 51841310

GTIN: 4026397490282



L'article n'est plus disponible.

Caractéristiques:

- Equipped with 15 x 15 W quadcolor LED with RGBW colors (Osram)
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- Supports RDM (Remote Device Management)
- 15, 22 or 38 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution
- 5 LED segments independently controllable (3 LEDs x 5 segments)
- Master dimmer
- Motorized zoom with 22° - 50° beam angle
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable

Logistique

EAN / GTIN: 4026397490282

Poids: 13,45 kg

Longueur: 0.48 m

Largeur: 0.44 m

Hauteur: 0.36 m

- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	280,00 W
Dimension:	Largeur : 24 cm Profondeur : 34,4 cm Hauteur : 44,5 cm
DMX channels:	15/22/38
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	18 Hz
LED number:	15
LED type:	15 W QCL
Beam angle:	22° - 50°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	250 x 344 x 445 mm
Weight:	11 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle