

FUTURELIGHT POS-6 Scan LED QCL

LED color changing bar with TILT movement and 8 W RGBW LEDs (4in1)

Réf. : 51841362

GTIN: 4026397479287



L'article n'est plus disponible.

Caractéristiques:

- Stepless vertical movement via control panel or DMX
- Equipped with 6 quadcolor LEDs in the colors red, green, blue and white
- 6, 8, 12 or 30 DMX channels selectable
- Each LED can be controlled individually
- Hanging as well as standing installation possible
- Functions: RGBW color mixture, color presets, 11 preset color temperatures, automatic color change, built-in programs, dimmer, strobe effect, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Automatic position correction
- Adjustable microphone sensitivity via Control Board
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LCD display and four operating buttons
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Commandé via stand-alone; DMX
- Déjà préprogrammé pour %: Light'J; LED PC-Control 512; Light Captain

Logistique

EAN / GTIN: 4026397479287

Poids: 4,20 kg

Longueur: 0.60 m

Largeur: 0.12 m

Hauteur: 0.26 m

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	55,00 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Commande:	Stand-alone; DMX
Préprogrammé dans:	Light´J; LED PC-Control 512; Light Captain
Angle de départ (1/2 pic):	36°
Couleur du boîtier:	Noir
Dimension:	Longueur : 56 cm Profondeur : 6,5 cm Hauteur : 19,6 cm
Poids:	3,75 kg
DMX channels:	6/8/12/30
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	30 Hz
LED type:	8 W QCL
LED number:	6
Maximum TILT-movement:	240°
Beam angle:	36°
Dimensions (L x W x H):	560 x 65 x 196 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle