

EUROLITE HE Laser software with EasyLase USB 2

PC laser show software EUROLITE HE V5 including EasyLase USB 2 interface

Réf. : 51885501

GTIN:



L'article n'est plus disponible.

Caractéristiques:

Logistique

PC laser show software EUROLITE HE V5 including EasyLase USB 2 interface

- Powerful PC laser show software
- CD-ROM with multi-language version
- Includes EasyLase USB 2 interface, dongle and USB cable
- Create stunning laser shows with EUROLITE HE V5 after a short familiarization for discos, bars, clubs, events, and concerts
- Several helpful for custom effects by the push of a button:
- Effect window (rotations on two independent layers, rotation center, compressing, intensity, image copying)
- 8 wave generators
- Path tool
- Stretch lines
- Texts as type crawl or morph effect
- SMS to Laser optional
- Sound-to-laser function for laser output to the beat of the music
- Supports DMX512 in and out
- Control via mouse, keyboard, MIDI and DMX controllers
- Free software updates
- CD-ROM includes award-winning laser shows
- Recommended hardware: laptop or desktop PC with Windows XP/Vista/7

EUROLITE HE Laser software incl. USB dongle

PC laser show software EUROLITE HE V5 including EasyLase USB 2 interface

- Powerful PC laser show software
- CD-ROM with multi-language version
- Includes USB dongle
- Create stunning laser shows with EUROLITE HE V5 after a short familiarization for discos, bars, clubs, events, and concerts
- Several helpful for custom effects by the push of a button:
- Effect window (rotations on two independent layers, rotation center, compressing, intensity, image copying)
- 8 wave generators
- Path tool
- Stretch lines
- Texts as type crawl or morph effect
- SMS to Laser optional
- Sound-to-laser function for laser output to the beat of the music
- Supports DMX512 in and out
- Control via mouse, keyboard, MIDI and DMX controllers
- Free software updates
- CD-ROM includes award-winning laser shows
- Recommended hardware: laptop or desktop PC with Windows XP/Vista/7

ACCESSORY EasyLase USB 2 laser interface

EasyLase USB 2 laser interface

- USB full speed Interface (12Mbits/Sec.)
- 1.5 Mbytes/Sec. maximum Datatransfer
- High Performance 32 Bit RISC-Microcontroller for fast dataprocessing
- X/Y outputs 12 Bits resolution, 16 millions framecoordinates totally
- Color outputs RGB, Intensity and 2 additional channels, 12 Bit each
- Active controlled shutter output
- Output speed up to 110000 points per second (pps) in 3+1 colour mode.
- Additional 8 Bit TTL-compatible digital output
- Power over USB or external 9-24V DC powersupply (500mA)
- ILDA-standard connector
- X/Y outputs symmetrical, colour outputs single ended
- Error-tolerant data protocol
- Plug and play driver for all Windows operating systems from XP, 64Bit also
- User API for driver DLL compatible with previous EasyLase.dll
- Supports 512 DMX-channels input and output
- DMX output at ILDA connector
- DMX input and output available at additional connector panel (optional)
- Firmware update over USB
- MicroSD card slot mounted for future showplayer options
- Supported by LDS Dynamics, Laser Design Studio, Mamba and HE-Laserscan Software

Données techniques:

Poids: 320 g
