

EUROLITE LED FLD-252 UV 10mm Flood

DMX controlled UV floodlight with 252 x 10 mm LED

Réf. : 51913862

GTIN: 4026397318777



L'article n'est plus disponible.

Description:

Black is beautiful!

It is almost scary, how rapidly the development of LEDs is advancing. Only the increased performances of computers or mobile phones may be slightly comparable. Anyway the diodes have revolutionized the lighting industry and pushed forward into every domain. Also in the field of black light, they put their ability to test. In this concern our LED Floodlight 252 UV is a clean proof. Not only is it amazingly powerful and thus creates an impressive UV light, but it also presents itself very versatile. It can be used for illuminating mirror balls, entrance or counter areas or as basic illumination. Due to the also delivered mounting bracket it can, moreover, be installed on a truss system. Eventually, the LEDs can as well convince with a flicker-free and pin sharp projection. Really scary these LEDs.

Logistique

EAN / GTIN: 4026397318777

Poids: 4,40 kg

Longueur: 0.54 m

Largeur: 0.23 m

Hauteur: 0.21 m

Caractéristiques:

- DMX512 control via standard DMX controller (occupies 2 channels)
- Equipped with 252 x 10 mm UV LEDs
- Sound-control via built-in microphone
- Adjustable dimmer and strobe functions
- Master/Slave function
- Rugged compact housing in a beautiful design
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Perfect in public places, main halls, lounges
- Mounting bracket for installation on a truss system included
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Effet UV
- Commandé via stand-alone; DMX

- Déjà préprogrammé pour %: Light´J
- Avec un Angle de départ de 40°

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	30 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Canaux DMX:	2
Commande:	Stand-alone; DMX
Préprogrammé dans:	Light´J
Angle de départ:	40°
Angle de départ (1/2 pic):	40°
Couleur du boîtier:	Noir
Matériau:	Métal
Dimension:	Largeur : 45,5 cm Profondeur : 12,5 cm Hauteur : 24 cm
Poids:	3,95 kg
DMX channels:	2
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	10 mm UV
LED number:	252
Beam angle:	40°
Dimensions (L x W x H):	125 x 455 x 240 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle