

## EUROLITE LED IP CCR-600 QCL Wall Light incl. Flight Case

PRO outdoor spotlight (IP65) in case with 60 x 8 W 4in1 LED (RGBW)

Réf. : 51914133

GTIN: 4026397573169



**L'article n'est plus disponible.**

### Caractéristiques:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via any standard DMX controller
- 4, 5, or 8 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- For architectural lighting
- Suitable for external use (IP65)
- For permanent installation
- Equipped with 60 x 4in1 QCL LED in the colors red, green, blue and white
- Stepless RGBW color blend
- Color macros
- Dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Internal programs
- Programmable color change speed
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection via power cord with 3-pin 16A CEE plug
- Flightcase included in delivery
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; W-DMX by Wireless Solution
- Déjà préprogrammé pour %: Light'J; LED PC-Control 512
- Exempt de scintillements
- Avec un Angle de départ de 15°
- Convient à une utilisation en extérieur IP65

### Logistique

EAN / GTIN: 4026397573169

Poids: 35,40 kg

Longueur: 0.74 m

Largeur: 0.34 m

Hauteur: 0.56 m

Article encombrant

## Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	230 W
Type de protection:	IP65
Type de lampe:	Lampe LED
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX; W-DMX by Wireless Solution
Préprogrammé dans:	Light'J; LED PC-Control 512
Projection:	Exempt de scintillements
Angle de départ:	15°
Angle de départ (1/2 pic):	15°
Angle de départ (1/10 pic):	48°
Couleur du boîtier:	Noir
Dimension:	Largeur : 64 cm Profondeur : 26,5 cm Hauteur : 43 cm
Poids:	35,30 kg
Protection grade:	IP65
DMX channels:	4/5/8
DMX connection:	3-pin XLR
Beam angle:	15°
LED type:	8 W QCL (R,G,B,W)
LED number:	60
Flash-rate:	18 Hz
Dimensions (L x W x H):	640x265x430mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle