

## EUROLITE LED SLS-145 TCL SMD 5050 Floor

Slimline LED spot with 145 SMD 3in1 LEDs

Réf. : 51915275

GTIN: 4026397448542



**L'article n'est plus disponible.**

### Description:

It is the popular KLS which has paved the path for Slim Line Spots. The KLS was the first successful attempt to replace bulky PAR spots by compact and flat ones - on a bar with 4 spots next to another. As is well known, the concept has been a raving success. As a logic consequence we also transformed the form of single spots - the SLS were born.

Obvious advantages of the SLS: they are slim. Compared to common PAR spots they considerably save space. For this reason they are much more flexible and handy. This is also true for installation, stock ground and transport - for most SLS we sell special cases which are smaller and cheaper than those for PAR spots. In the end, the design can save money.

Meanwhile Eurolite has built up a very rich assortment full of different spots. An assortment which is continuously enlarged. Every delivery finally includes a double bracket enabling an additional use as floor spot. Beside the different sizes of the spots the main differences can be seen in the illuminants. A choice of single LEDs, bicolor, tricolor and quadcolor LEDs is offered.

### Caractéristiques:

- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Compact construction with rugged plastic housing
- Equipped with 145 tricolor LEDs (SMD 5050) with RGB colors
- Wide beam angle provides high luminosity at a short distance
- 3 or 5 DMX channels selectable for various applications
- Functions: Static colors, RGB color blend, internal programs, dimmer, strobe effect, sound control, sensitivity
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone

### Logistique

EAN / GTIN: 4026397448542

Poids: 1,60 kg

Longueur: 0,29 m

Largeur: 0,27 m

Hauteur: 0,10 m

- Microphone-sensitivity adjustable via rotary control
- Control board with 4-digit display
- Ready for connection with power cord and safety plug
- DMX control via every standard DMX controller
- Commandé via stand-alone; DMX; Commande de la musique via Microphone
- Déjà préprogrammé pour %: Light`J

## Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	35 W
Type de protection:	IP20
Type de lampe:	Lampe LED
Fréquence du flash:	1 - 30 Hz
Canaux DMX:	3
Commande:	Stand-alone; DMX; Commande de la musique via Microphone
Préprogrammé dans:	Light`J
Angle de départ (1/2 pic):	80°
Couleur du boîtier:	Noir
Dimension:	Largeur : 25,3 cm Profondeur : 6,2 cm Hauteur : 27,6 cm
Poids:	1,30 kg
DMX channels:	3/5
DMX connection:	3-pin XLR
Sound control:	via built-in microphone
Flash rate:	30 Hz
LED number:	145
LED type:	TCL, SMD 5050
Beam angle:	80°
Dimensions (W x D x H):	253 x 62 x 276 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle