

EUROLITE Girder clamp 5000 kg black

Beam clamp

Réf. : 58011092

GTIN: 4026397400274



L'article n'est plus disponible.

Caractéristiques:

- Suitable as temporary installation point for steel beams (L-beams, I-beams)
- Quick and tool free installation of rigging points for spots, projectors, speaker-systems, screens, truss elements, motors, guide pulleys, chain hoists and decoration material
- Large flange range
- High carrying capacity
- Flexible use due to wide adjustment range
- Inexpensive attachment without drilling or welding
- Regularly tested by an independent and accredited testing institute
- Safety instruction: Beam clamps are not suitable for lifting or transporting I-beams!
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Logistique

EAN / GTIN: 4026397400274

Poids: 12,15 kg

Longueur: 0.35 m

Largeur: 0.15 m

Hauteur: 0.40 m

Données techniques:

Charge maximale BGV C1 (8 fois):	2500 kg
Charge maximale WLL (4 fois):	5000 kg
Ouverture:	90-310 mm
Dimension:	Longueur : 37 cm Largeur : 13 cm Hauteur : 33 cm
Poids:	11,65 kg
Maximum load BGV C1 (10-fold):	2000 kg

Maximum load BGV C1 (12-fold):	1666 kg
Flange range:	90-310 mm
Dimensions:	370 x 130 x 330 mm