

EUROLITE LCD-4/S Dimmer controller

Commande d'éclairage à 4 canaux

Réf. : 70062661

GTIN: 4026397179095



L'article n'est plus disponible.

Caractéristiques:

- 4 channels
 - Fade Time fader with LED for adjusting the step time
 - Master-fader with LED for adjusting the total output level
 - Audio-fader with LED for adjusting the music sensitivity
 - Flash-button per channel and master-flash (Full On-button)
 - LED-display of all modes
 - 0/10 V-output via one 8-pin DIN-socket
 - 42 built-in programs
 - Dimmer: Manual control of the channels via sliders
 - Full On: all channels can be switched on together
 - Program speed adjustable via speed-fader or Tap Sync-button
 - Sound-control via external signal or integrated microphone
 - Sound to light via RCA socket
 - Outputs via 4 safety sockets
 - Rack installation with 3 units
 - Only for professional use
- Appareil**
- Sans fil, flexible et polyvalent
- L'étendue des fournitures**
- 1 x appareil

Logistique

EAN / GTIN: 4026397179095

Poids: 5,15 kg

Longueur: 0.52 m

Largeur: 0.20 m

Hauteur: 0.21 m

Données techniques:

Alimentation électrique:

230 V AC, 50 Hz

Dimension: Largeur : 48,3 cm
Profondeur : 14,5 cm
Hauteur : 13,35 cm

Appareil

Type de batterie:	1 x Nickel-Cadmium 3,6 V,
Max. power output:	3680 W
Max. current:	16 A
Number of control channels:	4
Max. output/channel:	1150 W
Max. current/channel:	5 A
Integrated programs:	42
Sound-control:	via built-in microphone or via audio-input
Audio-input:	RCA socket
Audio-sensitivity:	0.1-1 V
Output sockets:	4 safety sockets
Fuse:	4 x F 6.3A, 250 V
Dimensions (W x D x H):	482 x 145 x 132 mm
	Rack installation with 3 u
Minimum mounting depth:	230 mm
Weight:	4.5 kg
