

## EUROLITE LCD-4 DMX Dimmer controller

Lighting controller 4 channels

Réf. : 70064590

GTIN: 4026397119039



**L'article n'est plus disponible.**

### Caractéristiques:

- Can be used as DMX controller or analog lighting controller (4 channels)
  - 4 channel-faders with LED
  - Fade Time fader with LED for adjusting the step time
  - Master-fader with LED for adjusting the total output level
  - Audio-fader with LED for adjusting the music sensitivity
  - Flash-button per channel and master-flash (Full On-button)
  - LED-display of all modes
  - 0/10 V-output via one 8-pin DIN-socket
  - 42 built-in programs
  - Dimmer: Manual control of the channels via sliders
  - Full On: all channels can be switched on together
  - Program speed adjustable via speed-fader or Tap Sync-button
  - Sound-control via external signal or integrated microphone
  - External signal connection via RCA socket
  - Power supply via included power unit or via 18-20 V dimmer pack
  - Rack installation
  - Only for professional use
- Appareil**
- Sans fil, flexible et polyvalent
- L'étendue des fournitures**
- 1 x appareil

### Logistique

EAN / GTIN: 4026397119039  
Poids: 2,80 kg  
Longueur: 0,55 m  
Largeur: 0,24 m  
Hauteur: 0,15 m

## Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	6,00 W
Dimension:	Largeur : 48,3 cm Profondeur : 13,35 cm Hauteur : 6,5 cm
Appareil	
Type de batterie:	1 x Nickel hydrure métallique 3,6 V, via 15-18 V DC, 300 mA power unit included in the delivery or optional dimmer-pack
Number of control channels:	4
Integrated programs:	42
Sound-control:	via built-in microphone or via audio-input
Audio-input:	RCA
Audio-sensitivity:	0.1-1 V
DMX512 output:	3-pin XLR connector
Analogue output:	8-pin DIN-socket, 4 channels
Output voltage:	0/10 V DC
Dimensions (L x W x H):	483 x 132 x 65 mm Rack installation with 3 u
Minimum mounting depth:	90 mm
Weight:	2 kg