

## OMNITRONIC MPZ-500 PA mixing amplifier

Amplificateur mélangeur (système de sonorisation) 4 zones, zones commutables, 500 W RMS

Réf. : 80709750

GTIN: 4026397220766



**L'article n'est plus disponible.**

### Caractéristiques:

- Comfortable control of your PA speakers via 4-zone technology
- 4 PA zone outputs, independently switchable on the front panel
- Master PA output (70 V and 100 V)
- Output for low-impedance speakers (4-16 ohms)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- Microphone input 3 with adjustable priority circuit
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-fold LED level display
- Master control for the output signal
- Fan-cooled
- Protection circuits with LED indication: over current, short circuit, turn-on delay
- Rack installation, brackets detachable

### Logistique

EAN / GTIN: 4026397220766

Poids: 17,60 kg

Longueur: 0.56 m

Largeur: 0.48 m

Hauteur: 0.20 m

### Données techniques:

|                          |                     |
|--------------------------|---------------------|
| Alimentation électrique: | 230 V AC, 50 Hz     |
| Puissance de sortie:     | 500 W RMS           |
| Plage de fréquence:      | 80 - 16000 Hz       |
| Sortie de la zone:       | 4 zones commutables |
| Dimension:               | Largeur : 48,3 cm   |

Profondeur : 38,5 cm  
Hauteur : 13,35 cm

---

|                    |                                  |
|--------------------|----------------------------------|
| Output power:      | 500 W RMS                        |
| Output type:       | 70 V, 100 V or 4-16 ohms         |
| Output current:    |                                  |
| 70 V               | 7 A                              |
| 100 V              | 5 A                              |
| Mic input:         | 5 mV, 600 ohms                   |
| Line input:        | 300 mV, 10 kohms                 |
| Output connectors: | Screw connectors, terminal block |
| Distortion:        | 0.5 % (1 kHz)                    |
| S/N ratio:         |                                  |
| Aux:               | 85 dB                            |
| Mic:               | 75 dB                            |
| Dimensions:        | 483 x 385 x 138 mm               |
| Weight:            | 22 kg                            |

---