

OMNITRONIC WMS-5S PA Wall Speaker

Enceinte 2 voies et support, Technologie PA 100 V, 40 W RMS

Réf. : 80710536

GTIN: 4026397523096



L'article n'est plus disponible.

Caractéristiques:

- 100 V technology with high-quality components for hifi sound
- 2-way bass-reflex system with 13 cm bass-midrange speaker (5") and 2.5 cm tweeter (1")
- Suitable for 100 V or 8-ohm operation
- 4-step power selector
- Weather-proof plastic cabinet (IP44) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket
- Loose cable ends
- For outdoor and indoor amplifying systems

Logistique

EAN / GTIN: 4026397523096

Poids: 4,25 kg

Longueur: 0.34 m

Largeur: 0.24 m

Hauteur: 0.19 m

Données techniques:

Type de protection:	IP44
Capacité de charge:	Programme: 80W Nominale: 40W RMS (8 Ohm) Nominale: 40W RMS (PA 100 V)
Plage de fréquence:	70 - 20000 Hz
Sensibilité:	90 dB
Impédance:	Technologie PA 100 V; 8 Ohm
Prise de puissance:	5W; 10W; 20W; 40W RMS via Commutateur de sélection sélectionnable

Enceinte:	1 x Bousseur 5" Tweeter 1"
Type d'enceinte:	Boîtier compact
Dimension:	Largeur : 19,6 cm Profondeur : 15,7 cm Hauteur : 29,5 cm
Poids:	3,70 kg