

## OMNITRONIC WCS-800 Conference system

Système de conférence sans fil UHF à 8 canaux

Réf. : 8080001

GTIN: 4026397325348



**L'article n'est plus disponible.**

### Caractéristiques:

- Set includes receiver and 8 microphones with built-in transmitter
- Receiver:
  - Diversity system with two removable antennas (BNC connection)
  - Operation in the low-interference UHF-band (740-764 MHz)
  - 8 channels with separate level control and LEDs for carrier and audio signals
  - Balanced XLR output per channel
  - 6.3 mm output for mixed signal
  - Operation via supplied power unit
  - Incl. mounting brackets for 483 mm rack installation (1 U)
- Microphones:
  - Dynamic microphone capsule with cardioid characteristic in aluminum diecast housing
  - Operation via supplied 1.5 V batteries (type AA)

### Logistique

EAN / GTIN: 4026397325348

Poids: 11,20 kg

Longueur: 0.56 m

Largeur: 0.48 m

Hauteur: 0.17 m

### Données techniques:

|                                   |   |
|-----------------------------------|---|
| Puissance totale de raccordement: | 5,00 W  |
| Dimension:                        | Largeur : 28 cm<br>Profondeur : 21,2 cm<br>Hauteur : 4,4 cm |
| Poids:                            | 8,00 kg   |
| Batterie:                         | 16 x 1,5 V AA Mignon LR06 alcaline au manganèse ci-joint    |

|                          |                                     |
|--------------------------|-------------------------------------|
| System:                  |                                     |
| Carrier frequency:       | UHF 740-764 MHz                     |
| Coverage:                | 40 m (with line-of-sight)           |
| Frequency range:         | 60-16000 Hz ( $\pm 3$ dB)           |
| T.H.D.:                  | <1%                                 |
| Dynamic range:           | 90 dBA                              |
| Receiver:                |                                     |
| System:                  | Diversity, 8 channels               |
| Max. audio output level: | -18 dBV/ 3000 ohms (6.3 mm jack)    |
|                          | -12 dBV/ 600 ohms (XLR)             |
| Output impedance:        | 1 kohms (6.3 mm jack)               |
|                          | 200 ohms (XLR)                      |
| Sensitivity:             | <-92 dB                             |
| Power supply:            | 15-18 V DC, 1000 mA (receiver)      |
|                          | 230 V AC, 50 Hz (power supply unit) |
| Dimensions (H x W x D):  | 280 x 212 x 44 mm                   |
| Microphone:              |                                     |
| Polar pattern:           | Cardioid                            |
| RF power output:         | 10 mW                               |
| Max. audio input level:  | 0 dBV                               |
| Power supply:            | 1.5 V mignon battery, type AA       |
| Battery life:            | 8 hours (Alkaline)                  |
| Dimensions (H x W x D):  | 50 x 111 x 148 mm                   |

### Contenu de la livraison:

1 x microphone