

EUROLITE Relai commandé par vidéo LVH-8

Relai commandé par vidéo

Réf. : 81013208

GTIN: 4026397324846



Prix de catalogue: 31.95 €

TVA 19% incl.

Description:

VIDEO CONTROLLED RELAY

The LVH-8 serves as a video presence detector for an audio/video system. The unit generates a control signal based on the absence or presence of valid video signals. The unit responds to NTSC and PAL signals and features a feed-through output. Power connections are made using block terminals.

Logistique

EAN / GTIN: 4026397324846

Poids: 0,09 kg

Longueur: 0.09 m

Largeur: 0.04 m

Hauteur: 0.05 m

Caractéristiques:

- Détection de signaux vidéo
- Compatible NTSC et PAL
- Pontage ou terminaison de ligne
- Indicateur de contrôle LED
- Alimentation en tension 12–24 V CC par bornes à vis (bloc d'alimentation non inclus)
- Extrêmement compact

Données techniques:

Alimentation électrique: 12-24 V CC 74 mA

Connexions: 2 x BNC (F)
Borne à visser

Dimension: Largeur : 7,6 cm
Profondeur : 4,1 cm
Hauteur : 3,1 cm

| | |
|------------------------------------|--|
| Poids: | 70 g |
| 1 x video input: | 0.5-1 Vpp/75 ohms BNC, ground referenced |
| 1 x video output: | Feed-through/ BNC, ground referenced |
| Control output: | N/O or N/C contacts |
| Relay contacts: | Single-pole, double-throw |
| Max. switching power: | 60 W, 125 VA |
| Max. switching voltage: | 220 V AC, 250 V DC |
| Max. switching current: | 2 A |
| Max. continuous switching current: | 3 A |