



Description:

Basics:

GS=Gap Short (shortened electrode space)

DE=Double Ended (double-sided lamp with threaded pin)

SE=Single Ended (one-sided lamp)

PAR=Lamp built in a parabolic reflector

HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Logistique

EAN / GTIN: 4026397139846

Poids: 0,08 kg

Longueur: 0.15 m

Largeur: 0.06 m

Hauteur: 0.04 m

Caractéristiques:

- Bon indice de rendu de couleur (IRC)

Données techniques:

Tension de service: 95

Tension nominale: 575 W

Culot/douille: GX9.5

Type de lampe: Lampe à décharge

Température de couleur: 7200K

Rendu de couleur (CRI): 85 Ra

Position de fonctionnement:	S180 (universal)
Durée de vie:	500 h
Flux lumineux:	49000 lm
Courant de la lampe:	7 A
Dimensions (LxD):	125x28 mm
Poids:	0,05 kg
Catégorie d'efficacité énergétique (A - G):	G
EPREL-Nr:	1612602

Contenu de la livraison:
