

PHILIPS MSR 1200 100V/1200W G-22 800h

Ampoules HMI/MSR/HMP/OMI

Réf. : 89109015

GTIN: 8711500189363



L'article n'est plus disponible.

Description:

Basics:

GS=Gap Short (shortened electrode space)

DE=Double Ended (double-sided lamp with threaded pin)

SE=Single Ended (one-sided lamp)

PAR=Lamp built in a parabolic reflector

HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Logistique

EAN / GTIN: 8711500189363

Poids: 0,28 kg

Longueur: 0,23 m

Largeur: 0,12 m

Hauteur: 0,10 m

Caractéristiques:

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Bon indice de rendu de couleur (IRC)
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Tension de service: 100 V

Tension nominale: 1200 W

Culot/douille: G-22

Type de lampe: Lampe à halogénures métalliques

Température de couleur: 5900K

Rendu de couleur (CRI): 80 Ra

Position de fonctionnement: S180 (universal)

Durée de vie: 800 h

Flux lumineux: 110000 lm

Dimensions (LxD): 175x40 mm

Poids: 160 g

Spécifications juridiques

Produit spécial: Non destiné à l'éclairage de la pièce dans les ménages

Utilisation: Éclairage pour effets de spectacle
