

## OMNILUX MR-11 12V/20W G-4 FL FTC

Ampoule pour miroir, lumière froide

Réf. : 91205880

GTIN: 4026397101485



**L'article n'est plus disponible.**

### Caractéristiques:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Color temperature 3200° K
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Inside the lamp, there is a temperature of up to 1400° Celsius
- Different illumination angles for different application areas
- Low power consumption
- Average lifetime 2000 h
- Dimmable
- Inflammable à chaud
- Indice de rendu de couleur (IRC) très élevé

### Logistique

EAN / GTIN: 4026397101485

Poids: 0,02 kg

Longueur: 0.04 m

Largeur: 0.04 m

Hauteur: 0.04 m

### Données techniques:

Tension de service: 12 V

Tension nominale: 20 W

Culot/douille: G-4

Type de lampe:	Lampe halogène; Lampe à verre transparent; Lampe à basse tension; Lampe à gaz à piston; Ampoule halogène; Lampe Cool Beam
Spécification de l'ampoule:	Dimmable Inflammable à chaud
Angle de départ:	18°
Couleur lumineuse:	Blanc
Température de couleur:	3200K
Rendu de couleur (CRI):	95 Ra
Durée de démarrage:	0 s
Construction:	Réflecteur; Culot à broche
Température de fonctionnement max.:	40° C
Température de fonctionnement min.:	20° C
Position de fonctionnement:	S180 (universal)
Durée de vie:	2000 h
Dimensions (LxD):	35x33 mm
Spécifications juridiques	
Catégorie d'efficacité énergétique (A++ - E):	D