

OMNITRONIC LXO-23 Active Crossover

High-quality active stereo crossover with limiter

Art.n.: 10355640

GTIN: 4026397433654



L'articolo non è più disponibile.

Features :

- 2-way stereo or 3-way mono operation possible
- Limiter adjustable from -40 to 22 dB
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low cut switch
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation
- Montaggio su rack (19") 48,3 cm 1 U

Logistica

EAN / GTIN: 4026397433654

Peso : 2,65 kg

Lunghezza : 0.54 m

Larghezza : 0.20 m

Altezza : 0.08 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	10,00 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Intervallo di frequenza:	45 - 9000 Hz

Struttura della custodia:	Montaggio su rack (19") 48,3 cm 1 U
Misure:	Larghezza: 48,3 cm Profondità: 14,7 cm Altezza: 4,45 cm
Peso:	2,30 kg
Limiter:	-40-22 dBu
Slope:	24 dB / octave
Operation modes:	2-way stereo or 3-way mono
Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	-- to +6 dB
Output gain:	-- to +12 dB
Low Cut:	30 Hz, -3 dB
Phase adjustment:	0-180°