

## OMNITRONIC SMA-600 Amplifier

Stereo PA amplifier with limiter and SMPS, 2 x 300 W/4ohms

Art.n.: 10451082

GTIN: 4026397606058



### Descrizione :

#### Weight Watcher!

Weight reduction, a wish certainly shared by many. Generally speaking, it's all about comfort. Whether it's packed luggage, cellular phones, cameras or even amplifiers. That's right, amplifiers, too. Whoever has installed a sound system before, can really appreciate light-weight devices as opposed to an aching back. Our recommendation: the new SMA-Amplifier Series from OMNITRONIC. By virtue of its switch-mode power supply technology, it saves an enormous amount of weight, comparing to many other amplifiers. If only three amplifiers are built into a rack, differences of 30kg or more can be achieved. A factor not to be underestimated, also when transporting. After all, payload weight equally needs to be considered. But not only due to its weight, the SMA-Series also convinces due to its functions as well as its power for mid-sized and larger applications. Just give it a try, its worth it!

### Features :

- Low weight and height due to integrated switch-mode power supply
- Temperature-controlled fan, particularly quiet during operation
- Limiter and speaker switch-on delay
- Switchable bass-boost at 80 Hz with 6 dB level increase
- 3 operating modes can be selected (stereo, parallel or bridged)
- Selectable input sensitivity
- 2 level controls
- 3 LEDs for each channel for activated protective circuit (protect) overload (clip) and signal
- 2 LEDs for parallel and bridge operation
- Complete protection set against short-circuit, overheat, DC voltage and VHF signals
- Electronically balanced inputs via XLR mounting jacks, with feed-through output (stereo RCA/6.3 mm jack)

### Logistica

EAN / GTIN: 4026397606058

Peso : 8,50 kg

Lunghezza : 0.60 m

Larghezza : 0.52 m

Altezza : 0.19 m

- Speaker outputs via lockable Speaker plugs
- Class AB circuitry
- Robust steel chassis
- Rack installation with 2 units
- Montaggio su rack (19") 48,3 cm

## Dati tecnici :

|                            |                                                                                                                            |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Alimentazione elettrica:   | 230 V AC, 50 Hz                                                                                                            |
| Potenza totale installata: | 421,00 W                                                                                                                   |
| Potenza in uscita:         | Massimo 648 W<br>2 x 324 W RMS (4 Ohm)<br>2 x 231 W RMS (8 Ohm)                                                            |
| Commutazione:              | Class H                                                                                                                    |
| Struttura della custodia:  | Montaggio su rack (19") 48,3 cm                                                                                            |
| Misure:                    | Larghezza: 48,3 cm<br>Profondità: 34 cm<br>Altezza: 8,9 cm                                                                 |
| Peso:                      | 5,75 kg                                                                                                                    |
| Power output sine:         |                                                                                                                            |
| stereo 4 ohms              | 2 x 324 W                                                                                                                  |
| stereo 8 ohms              | 2 x 231 W                                                                                                                  |
| 8 ohms bridged             | 1 x 600 W                                                                                                                  |
| Frequency range:           | 20-20000 Hz, $\pm 0.5$ dB                                                                                                  |
| Damping factor:            | >150                                                                                                                       |
| Distortion factor:         | 0.05 %                                                                                                                     |
| Slew rate:                 | >20 V/ $\mu$ sec                                                                                                           |
| S/N ratio:                 | >90 dB                                                                                                                     |
| Channel separation:        | >65 dB/ 1 kHz                                                                                                              |
| Input sensitivity:         | 26 dB/32 dB (2.2 V/1.05 V), switchable                                                                                     |
| Voltage gain:              | 26 dB/32 dB                                                                                                                |
| Input impedance:           | 20 kohms (balanced), 10 kohms (unbalanced)                                                                                 |
| Input connectors:          | stereo XLR                                                                                                                 |
| Output connectors:         | stereo Speaker, feed-through output (stereo RCA, stereo 6.3 mm jack)                                                       |
| Circuitry:                 | class AB                                                                                                                   |
| Control elements:          | power switch, level control per channel, mode switch (stereo/parallel/bridged), sensitivity selector, peak filter selector |
| LED indicators:            | parallel, bridge (globally), protect, clip, signal (per channel)                                                           |
| Protection circuits:       | short-circuit, overheat, DC voltage, VHF signals, softstart                                                                |
| Construction:              | steel chassis                                                                                                              |
| Dimensions (DxWxH):        | 340 x 483 x 92 mm (19", 2 U)                                                                                               |

**Contenuto della confezione:**

---