

## OMNITRONIC DJP-700 Class D Amplifier

Compact stereo mixing amplifier, 2 x 300 W / 4 ohms

Art.n.: 10451601

GTIN: 4026397563306



**L'articolo non è più disponibile.**

### Features :

- For quick-access music playback control in restaurants, fitness studios and retail locations
- Efficient class D circuitry
- Silent operation due to fanless cooling concept
- Extremely low weight and height due to integrated switch mode power supply
- 2 operating modes can be selected (stereo or bridged)
- Speaker switch-on delay and auto limiters
- 4 stereo line inputs
- 1 mono microphone input with gain control on the front panel
- Additional 3.5 mm connection on the front panel
- Audio source selector
- Controls for volume, bass and treble
- Stereo master output
- Extensive protective circuits
- Robust steel chassis with aluminum front panel

### Logistica

EAN / GTIN: 4026397563306

Peso : 2,76 kg

Lunghezza : 0.34 m

Larghezza : 0.28 m

Altezza : 0.08 m

### Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 130 W 1/8 Power

Potenza in uscita: 2 x 200 W RMS (8 Ohm)  
2 x 300 W RMS (4 Ohm)

Commutazione: Class D

Equalizzatore: Master: 1 x regolatore a 2 bande Stereo

|                      |                                                                                  |
|----------------------|----------------------------------------------------------------------------------|
| Misure:              | Larghezza: 25,6 cm<br>Profondità: 23,3 cm<br>Altezza: 4,45 cm                    |
| Peso:                | 2,36 kg                                                                          |
| Power output sine:   |                                                                                  |
| stereo 4 ohms        | 2 x 300 W                                                                        |
| stereo 8 ohms        | 2 x 200 W                                                                        |
| 8 ohms bridged       | 1 x 600 W                                                                        |
| Frequency range:     | 20-20000 Hz, $\pm 0.5$ dB                                                        |
| Damping factor:      | >300                                                                             |
| Distortion factor:   | 0.05 %                                                                           |
| Slew rate:           | 14 V/ $\mu$ sec                                                                  |
| S/N ratio:           | 100 dB                                                                           |
| Input impedance:     | 20 kohms (balanced), 10 kohms (unbalanced)                                       |
| Input sensitivity:   | 1 V                                                                              |
| Input connectors:    |                                                                                  |
| Line 1-4:            | RCA L/R                                                                          |
| Mic:                 | combination XLR/6.3 mm jack, unbal.                                              |
| Aux:                 | 3.5 stereo jack                                                                  |
| Output connectors:   |                                                                                  |
| Master:              | RCA L/R                                                                          |
| Speaker:             | screw connectors                                                                 |
| Circuitry:           | class D                                                                          |
| Control elements:    | power switch, source selector, level/tone controls, mode switch (stereo/bridged) |
| LED indicators:      | power                                                                            |
| Protection circuits: | softstart, short-circuit, overheat, clipping, overload, VHF signals, DC voltage  |
| Construction:        | steel chassis, aluminum front                                                    |
| Dimensions (DxWxH):  | 256 x 233 x 44 mm                                                                |