

OMNITRONIC DD-4750 USB turntable

Direct drive DJ turntable with USB interface and recording software

Art.n.: 10603020

GTIN: 4026397356076



Features :

- Direct drive high-torque motor
- Quartz-controlled for highest speed precision
- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Plug & play: no driver installation required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Quick start
- 2 large start/pause buttons
- Selectable quartz-controlled pitch lock
- Motor with reverse run can be switched off
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing feet
- Switchable phono/line output
- Delivery includes pick-up system, slipmat, RCA and USB cable
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Delivery without dust cover

Logistica

EAN / GTIN: 4026397356076

Peso : 10,90 kg

Lunghezza : 0.52 m

Larghezza : 0.43 m

Altezza : 0.20 m

Dati tecnici :

Alimentazione elettrica:	115/230 V AC, 50/60 Hz
Potenza totale installata:	13,50 W
Intervallo di frequenza:	50 - 20000 Hz
Misure:	Larghezza: 44,9 cm Profondità: 37 cm Altezza: 14,5 cm
Peso:	9,80 kg
Type:	manual turntable
Drive method:	quartz-controlled direct drive
Motor:	brushless DC motor
Turntable platter:	d=330 mm, aluminum diecast
Speed:	33 1/3 RPM, 45 RPM and 78 RPM
Change time between speeds:	<0.3 sec
Initial torque:	>3.5 kg/cm
Start time:	<0.3 sec
Brake:	electronic brake
Stop time:	<0.3 sec
Pitch adjustment:	±10 %, ±20 %, ±50 %
Wow and flutter:	<0.1 %
Rumble:	55 dB DIN B
Tone arm:	S-shape with Cardan's suspension
Tone arm length:	230 mm
Overhang:	15 mm
Anti-skating range:	0-4 g
Applicable cartridge weight:	6-10 g
Stylus pressure range:	3-4 g
Phono output level:	1.5-3.6 mV/ 1 kHz 5 cm/sec
Line output level:	90-216 mV/ 1 kHz 5 cm/sec
Channel separation:	>15 dB
Output connectors:	RCA, USB type B
Dimensions:	449 x 370 x 145 mm

Contenuto della confezione: