

OMNITRONIC PMS-10 Studio subwoofer

The completion for your studio monitors

Art.n.: 11036468

GTIN: 4026397222517



L'articolo non è più disponibile.

Features :

- Suitable for PMM-4, PMM-5, PMM-8, PSM-6.5, PSM-6.5A and all other passive systems in need of bass support
- High efficiency
- Stereo input (XLR/6.3 mm jack)
- Stereo output and feed-through output (both XLR)
- Active 2-way crossover
- Level control
- Phase inversion switch
- High-pass filter, selectable via footswitch
- Standby mode

Logistica

EAN / GTIN: 4026397222517

Peso : 17,40 kg

Lunghezza : 0.55 m

Larghezza : 0.53 m

Altezza : 0.44 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	250 W
Intervallo di frequenza:	40 - 350 Hz
Collegamenti:	Ingresso: Altoparlante via 1 x XLR a 3 poli Ingresso: Altoparlante via 1 x Jack da 6,3 mm (non sim.)
Altoparlante:	1 x 10" Woofer
Misure:	Larghezza: 43 cm Profondità: 43 cm

	Altezza: 31,5 cm
Peso:	15,50 kg
Amplifier power:	150 W
Components:	25 cm woofer (10")
Inputs:	XLR/6.3 mm jack
Outputs:	XLR
Footswitch:	6.3 mm jack
Distortion factor:	0.05 %
Min. input sensitivity:	0.775 V
Input impedance:	4 ohms
Dimensions (H x W x D):	430 x 430 x 315 mm