

OMNITRONIC ASS-1503 Active System

Powerful mobile column PA system, 850 W RMS

Art.n.: 11038851

GTIN:



Features :

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in no time
- Convinces with excellent speech reproduction and wide coverage
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (500 W + 350 W RMS) with SMPS
- 38 cm bassreflex subwoofer
- Fullrange column speaker with 12 x 8 cm drivers
- Balanced 6.3 mm jack input and parallel XLR output
- Master level control with peak indication
- Adjustable crossover frequency for subwoofer
- Phase switchable for subwoofer
- Subwoofer with plywood enclosure
- Column speaker with MDF enclosure
- Scratch-resistant lacquer surface, impact-resistant steel grille and flange
- Delivery includes distance tube, speaker cable and power cable
- Castor set and wheel board available as accessory
- Rotelle opzionali

Logistica

Dati tecnici :

Potenza totale installata:	200 W
Altoparlante:	1 x 15" Woofer
Ausilio di trasporto:	Rotelle opzionali

Peso:	40,40 kg
Power supply:	115/230 V AC, 50/60 Hz
Power output sine:	
Subwoofer:	500 W RMS
Satellite speaker:	350 W RMS
Components:	
Subwoofer:	38 cm woofer (15")
Satellite speaker:	12 x 8 cm mid-high driver (12 x 3")
Maximum SPL:	
Subwoofer:	122 dB
Satellite speaker:	121 dB
Frequency range:	
Subwoofer:	45-180 Hz
Satellite speaker:	120-20000 Hz
Crossover frequency:	40-160 Hz
Microphone input:	combination XLR/6.3 mm jack, bal.
Line input:	combination XLR/6.3 mm jack, bal. and RCA L/R
Speaker output:	1 x speaker, 4 ohms

Contenuto della confezione:
