

## OMNITRONIC TMC-1 MK2 Controller incl.VDJ

MIDI controller incl. software Virtual DJ 7 LE

Art.n.: 11045041

GTIN: 4026397431056



### Features :

- USB MIDI controller for DJs
- Play, mix and scratch digital audio like vinyl records
- Compatible to any MIDI controlled audio software, all MIDI controllers can be edited and freely assigned
- Optimized for control of the powerful audio and video mixing software Virtual DJ
- Supplied with Virtual DJ 7 Limited Edition, can be upgraded at discount price
- Supports all standard codecs, e.g. MP3, WAV, WMA, OGG, M4A, AAC, AVI, MPEG
- 2-channel mixer section:
  - 3-band EQ, gain control and level fader per channel
  - Ultra-smooth crossfader with adjustable curve
  - Cue function with 3 hot cues
  - LED level display
- Extra large track encoder for quick music library browsing
- Dual player section:
  - Touch-sensitive jog dials with mode selector: pitch bend, scratch, fast search
  - Automatic beat detection and beat mixing
  - Beat-accurate loops and samples
  - Master Tempo (tonal pitch remains constant)
  - Effect units with controls for selection and parameters
  - Sample players with LED display, and controls for selection and level
- Powered via USB or included PSU
- Incl. USB cable
- Fully functional home version of the software available under [virtualdj.com](http://virtualdj.com)
- Minimum system requirements PC: Windows XP(SP2)/Vista/7 (32-bit/64-bit), Pentium IV, 1.6 GHz processor, 1 GB RAM or better

### Logistica

EAN / GTIN: 4026397431056

Peso : 2,45 kg

Lunghezza : 0.41 m

Larghezza : 0.32 m

Altezza : 0.12 m

- Minimum system requirements Mac: OS X 10.4.11, Core Duo, 1.66 GHz processor, 1 GB RAM or better
- Frequenza di campionamento: 48 kHz

### Dati tecnici :

Frequenza di campionamento:	48 kHz
Collegamento USB:	USB 2.0, type B
Convertitore:	16 bit
Misure:	Larghezza: 36 cm Profondità: 26 cm Altezza: 7 cm
Peso:	1,90 kg
Type:	USB MIDI controller
	5 V DC, 500 mA via USB port or
	5 V DC, 1000 mA via supplied PSU
USB port:	2.0, type B
Converter:	16 bits
Sample rate:	48 kHz
Dimensions:	360 x 260 x 70 mm

### Contenuto della confezione: