

## OMNITRONIC TM-1000 Pocket transmitter

Trasmettitore tascabile con trasmettitore multifrequenza PLL

Art.n.: 13055510

GTIN: 4026397142754



### Descrizione :

For the rough stage use

The TM-1000 pocket transmitter comes in a rugged metal housing and withstands every rough stage use. A robust case with foam padding is included for save transport.

### Features :

- Matches receiver DR-1000 with the same carrier frequency
- Suitable for lavalier microphones or headsets with mini XLR plug
- Operation in the low-interference UHF band (790.000-814.000 MHz)
- 193 carrier frequencies switchable in 125 kHz steps
- Transmitting power 10 mW, operation range 100 meters
- System expandable to up to 16 receivers with 16 transmitters
- LCD for battery status and frequency
- Automatic frequency scan
- Sensitivity adjustable
- Lock function avoids undesired changes by users
- Mute mode when signal is absent or too weak
- Operation via 2 x 1.5 V mignon batteries (type AA)
- Can also be used for direct instrument pickup
- License-free and approved in Germany

### Dati tecnici :

### Logistica

EAN / GTIN: 4026397142754

Peso : 0,91 kg

Lunghezza : 0.37 m

Larghezza : 0.17 m

Altezza : 0.09 m

|                      |  |
|----------------------|--|
| Pila:                | 2 x 1,5 V AA Mignon R06 zinco-carbone presente             |
| Banda di frequenza:  | UHF  |
| Misure:              | Larghezza: 9,7 cm<br>Profondità: 6,4 cm<br>Altezza: 2,4 cm |
| Antenna:             | Built-in   |
| Carrier frequency:   | UHF 790.000-814.000 MHz                                    |
| Switching bandwidth: | 24 MHz   |
| No. of frequencies:  | 192  |
| Frequency steps:     | 125 kHz  |
| Modulation:          | FM   |
| Frequency stability: | ±0,005 %   |
| T.H.D.:              | <1 % at 1 kHz  |
| Tone signal:         | 32.768 kHz   |
| AF response:         | 40-18000 Hz  |
| Maximum deviation:   | ±48000 Hz  |
| RF power output:     | <10 mW   |
| Coverage:            | 100 m (with line-of-sight)                                 |
| Current consumption: | 100 mA   |
| Connection:          | 3-pin mini XLR   |
| Weight:              | 680 g  |

#### **Contenuto della confezione:**

---