

# PSSO®

---

## Prime Set XL

Art.n.: 20000514

GTIN:



---

Alle Rechte vorbehalten. Technische Änderungen und Irrtum vorbehalten.  
Alle Bilder ähnlich, zum Teil Symbolfotos.

# PSSO®

---

## Prime Set XL

Art.n.: 20000514

GTIN:

### Features :

---

#### PSSO PRIME-212 Club Speaker System

PRO PA speaker, 2 x 12" woofer, 1.5" horn, 1100 W RMS (Biamp)

- Rugged pro PA speaker, qualified for suspension and clubs
- Biamp operation
- Housing made of 18 mm (13 layers) and 25 mm (17 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.5"), 72 mm voice coil (2.8")
- Bassreflex system
- Neutrik Speakon connectors
- Scratch-resistant lacquer surface
- Applications: standing or suspended
- Driver di CELTO ACOUSTIQUE
- Realizzato in europa

**PSSO PRIME-182 Subwoofer 3000W**

PRO PA bassreflex subwoofer, 2 x 18" woofer, 3000 W RMS, 4 ohms

- Rugged pro bassreflex subwoofer, qualified for clubs and touring applications
- Housing made of 25 mm (17 layers) and 18 mm (13 layers) birch plywood
- 2 x 45 cm (18") bass speaker, 115 mm voice coil (4.5"), diecast aluminum basket
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Parallel Neutrik Speakon connectors
- Metal flange for top speakers
- Carrying handles and rubber feet
- Scratch-resistant lacquer surface
- Driver di CELTO ACOUSTIQUE
- Realizzato in europa

### **PSSO PRIME System Amplifier DSP**

Amplificatore di sistema multicanale class D con alimentatore switching, 4 x 400 W RMS (8 Ohm), 4 x 800 W RMS (4 Ohm)

- 6-channel PA amplifier with high-performance DSP, freely programmable
- Sample frequency: 96 kHz and 64-bit technology
- Premium components ensure excellent sound features
- Efficient class D amplifier circuitry
- 2 Pascal amplifier modules
- 4 analog inputs and 2 digital AES/EBU interfaces (XLR)
- 4 analog link outputs (XLR)
- 2 Neutrik Speakon outputs