

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

Art.n.: 41606120

GTIN: 4026397455243



Features :

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 LED 100 W COB (chip-on-board) bianco caldo (WW)
- Dimmer
- Effetto stroboscopico
- Controllabile via DMX
- With a beam angle of 60°

Logistica

EAN / GTIN: 4026397455243

Peso : 4,95 kg

Lunghezza : 0.47 m

Larghezza : 0.20 m

Altezza : 0.29 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 260 W

Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	2 x 100 W COB (chip-on-board) bianco caldo (WW)
Frequenza di lampeggiamento:	1 - 20 Hz
Attrezzature:	Dimmer
Canali DMX:	1; 2; 4
Attivazione:	DMX
Fixtures disponibili per:	Light´J; LED PC-Control 512; Light Captain
Angolazione del fascio di luce (1/2 picco):	60°
Temperatura colore:	3200K
Colore della custodia:	Nero
Misure:	Larghezza: 42 cm Profondità: 14 cm Altezza: 24 cm
Peso:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Contenuto della confezione: