

## EUROLITE LED KLS-200 Compact-Light-Set

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

Art.n.: 42109700

GTIN: 4026397346077



**L'articolo non è più disponibile.**

### Descrizione :

As good as it gets!

We are not only talking about the benefits of the LED technology, we can set impressive examples, such as our premium EUROLITE light set, the KLS-200. Because the 432 LEDs, that split on four spots, don't need a huge and heavy housing as is the case with halogen headlights. Try to imagine the different measures of a CRT-TV and a LCD-TV: that's the best comparison. According to this, the whole construction shows up very compact, lightweighted and extremely flexible - whereas the stability is always guaranteed of course. The KLS-200 can easily be put in the also delivered bag, transported and assembled by just one person. A must-have for mobile DJs, who perform their art on weddings or as the case may be, and do set value on a compact, easily transported and highly luminous light set. A foot switch for a direct and individual control is optionally available. An unique and imposing solution, that will definitely be very popular.

### Features :

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 (preset, sound control, freeze, blackout)
- DMX512 control via regular DMX controller (occupies 15 channels)

### Logistica

EAN / GTIN: 4026397346077

Peso : 9,60 kg

Lunghezza : 1.27 m

Larghezza : 0.41 m

Altezza : 0.13 m

Merci voluminose

- Optimized for control with the optional control panel DMX LED Operator 4
  - Via DMX, each spot can be individually controlled
  - DMX functions: dimmer, automatic mode, music control, strobe effect
  - Addressing and setting via control panel with 4-digit LED display
  - Suited for installation on a lighting stand (not included)
  - Ideal for bands, stages or solo entertainers
  - Ready for connection with power cord and safety plug
  - 432 potenti LED 10 mm R/G/B<BR> Spot controllabili singolarmente
  - Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
  - Controllabile via stand-alone; DMX; telecomando a pedale cablato (opzionale)
  - Già pre-programmato con Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
  - With a beam angle of 25°
  - Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica
- Dotazione della fornitura**
- 1 x Proiettori, 1 x borsa

## Dati tecnici :

|                                             |                                                                                                                                                        |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentazione elettrica:                    | 230 V AC, 50 Hz                                                                                                                                        |
| Potenza totale installata:                  | 55 W                                                                                                                                                   |
| Grado di protezione:                        | IP20                                                                                                                                                   |
| Allacciamento elettrico:                    | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Tipo di lampada:                            | Lampada a LED                                                                                                                                          |
| Tipo di LED:                                | 432 x 10 mm R/G/B                                                                                                                                      |
| Canali DMX:                                 | 15                                                                                                                                                     |
| Raffreddamento:                             | Raffreddamento a convezione passiva                                                                                                                    |
| Attivazione:                                | Stand-alone; DMX; telecomando a pedale cablato (opzionale)                                                                                             |
| Pre-programmato con:                        | Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3                                                                      |
| Angolazione del fascio di luce:             | 25°                                                                                                                                                    |
| Angolazione del fascio di luce (1/2 picco): | 25°                                                                                                                                                    |
| Colore della custodia:                      | Nero                                                                                                                                                   |
| Peso:                                       | 8,65 kg                                                                                                                                                |
| Borsa                                       |                                                                                                                                                        |
| Misure:                                     | Larghezza: 120 cm<br>Profondità: 12 cm<br>Altezza: 38 cm                                                                                               |
| DMX connection:                             | 3-pin XLR                                                                                                                                              |
| TV spigot:                                  | D = 28 mm                                                                                                                                              |
| Dimensions (L x W x H):                     | 1110 x 55 x 295 mm                                                                                                                                     |
| Specifiche legali                           |                                                                                                                                                        |
| Prodotto speciale:                          | Non destinato all'illuminazione di ambienti domestici                                                                                                  |
| Destinazione d'uso:                         | Illuminazione per effetti speciali                                                                                                                     |