

EUROLITE LED TMH-61 Hypno Moving Head Beam

Beam with 4 hypno rings and 60 W LED in RGBW colors

Art.n.: 51785896

GTIN: 4026397592924



L'articolo non è più disponibile.

Features :

- Beam effect with a 60 W COB LED in RGBW colors and 4 hypno rings with altogether 88 RGB SMD LEDs
- Compact lightweight
- 12, 27 or 29 DMX channels selectable
- Stepless RGBW color mixture, color presets and color change
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Internal programs
- LED hypno rings with stepless RGB color mixture - each color and each ring can be controlled individually, color presets and color changes
- Automatic position correction
- Positioning within 630° PAN and 210° TILT
- PAN-angle switchable between 630° and 540°
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone, sensitivity adjustable
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- DMX512 control via every standard DMX controller
- Effetto Beam
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via stand-alone; DMX
- Già pre-programmato con Light' J; LED PC-Control 512; Light Captain
- Senza sfarfallio

Logistica

EAN / GTIN: 4026397592924

Peso : 6,25 kg

Lunghezza : 0.44 m

Larghezza : 0.28 m

Altezza : 0.35 m

- With a beam angle of 2,5°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	80 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a LED
Raffreddamento:	Ventola
Attivazione:	Stand-alone; DMX
Pre-programmato con:	Light´J; LED PC-Control 512; Light Captain
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	2,5°
Angolazione del fascio di luce (1/2 picco):	2,5°
Colore della custodia:	Nero
Misure:	Larghezza: 24,5 cm Profondità: 16,5 cm Altezza: 35 cm
Peso:	5,40 kg
DMX channels:	12/27/29
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	25 Hz
LED number:	1 x COB + 88 x SMD
LED type:	60 W COB, RGBW + RGB SMD
Maximum PAN-movement:	630°
Maximum TILT-movement:	210°
Dimensions (L x W x H):	165 x 245 x 350 mm
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali