

EUROLITE LED IP FL-50 COB RGB 60° RC

Brilliant COB outdoor floodlight (IP65) with LED technology

Art.n.: 51914618

GTIN: 4026397552744



Features :

- Add highlights to your house and garden
- Ideal LED luminary for indoor or outdoor use
- The weather-resistant housing also allows operation during bad weather
- For permanent installation, mounting bracket included
- Extremely compact housing in an appealing design
- Equipped with 1 COB RGB LED
- Beam reflection angle of 60°
- Ready for connection via power cord with safety-plug
- IR-remote control with an operation range of approximately 7 m included in delivery
- Automatic color change or manual program or color selection
- Built-in programs for color change and color fade
- Adjustable program speed and brightness
- Direct color selection for 15 preset colors + white
- Memory function for control programs via the Flash, Strobe, Fade and Smooth buttons of the IR remote control
- 1 LED 50 W COB (chip-on-board) 3in1 TCL RGB (miscela di colori omogenea)
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; Telecomando IR
- With a beam angle of 60°
- Adatto per uso esterno IP65

Logistica

EAN / GTIN: 4026397552744

Peso : 2,90 kg

Lunghezza : 0.28 m

Larghezza : 0.25 m

Altezza : 0.17 m

Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Potenza totale installata:	50 W
Grado di protezione:	IP65
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Lunghezza cavo:	Circa 1,7 m
Tipo di lampada:	Lampada a LED
Tipo di LED:	1 x 50 W COB (chip-on-board) 3in1 TCL RGB (miscela di colori omogenea)
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; Telecomando IR
Angolazione del fascio di luce (1/2 picco):	60°
Colore della custodia:	Nero
Colore:	Trasparente
Misure:	Larghezza: 28,2 cm Profondità: 23,3 cm Altezza: 14 cm
Peso:	2,70 kg
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato
Protection grade:	IP65
LED-Typ:	COB, RGB
LED number:	1
Beam angle:	60°
Maximum remote control range:	7 m
Dimensions (L x W x H):	140 x 282 x 233 mm
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Contenuto della confezione:

1 x Proiettori
1 x telecomando
1 x Manuale d'uso