

## EUROLITE Lifting Rope 2000x10mm

Corda di ancoraggio, corda di sicurezza, Safety

Art.n.: 58010492

GTIN: 4026397192933



### Descrizione :

EUROLITE Lifting ropes, safety bonds

The EUROLITE lifting ropes, safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The lifting ropes, safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The lifting ropes, safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can install and secure loads above persons with these lifting ropes, safety bonds in all areas where the BGV C1 is required.

Use as attachment gear

These ropes are stamped with a WLL describing the maximum load when used for general lifting purposes. For all areas where the BGV C1 is required, the correct lifting rope must be selected only by calculating with safety-factor 12. According to this calculation, the maximum load of this rope is 450 kg (single-stranded).

Use as safety bond

The correct safety bond must be selected only by table 9 of BGI 810-3:2007-03. According to this table, the maximum load of this safety bond is 100 kg.

### Logistica

EAN / GTIN: 4026397192933

Peso : 1,65 kg

Lunghezza : 0.25 m

Larghezza : 0.24 m

Altezza : 0.06 m

### Features :

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- 16 mm shackle included in the delivery
- 10 x 2000 mm
- WLL 1050 kg

- Test report according to DIN EN 10204 as download
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Fune con redancia e connettore
- Verificato LGA
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

#### Dati tecnici :

|                                    |                                           |
|------------------------------------|-------------------------------------------|
| Carico massimo WLL (5 volte sup.): | 1050 kg                                   |
| Struttura funicolare:              | 6 x 19 FC                                 |
| Classe di resistenza della fune:   | 1770                                      |
| Norma:                             | DIN EN 12385-4:2008-06, DIN 56927:2009-03 |
| Resistenza nominale della fune:    | 1770 N/mm <sup>2</sup>                    |
| Superficie dei fili:               | Zincato                                   |
| Colore:                            | Argento                                   |
| Intervallo di temperatura:         | -40° C - +100° C                          |
| Misure:                            | Lunghezza: 200 cm<br>Diametro: Ø 1 cm     |
| Peso:                              | 1,64 kg                                   |
| Peso in lunghezza:                 | 0,359 kg/m                                |

#### Contenuto della confezione: