

EUROLITE STC-480/150 Truss Lifter TÜV/GS

Rugged truss lifter for medium-heavy loads

Art.n.: 59007055

GTIN: 4026397277920



Descrizione :

The EUROLITE STC-series are truss lifters manufactured under strict TÜV monitoring. These lifts boast of high quality, extraordinary ruggedness, highest versatility and high stability. The production is monitored by the German TÜV SÜD which means that they comply with the highest safety standards.

The GS mark signals to the buyer, customer, or consumer that the chosen product as well as the user manual and production (process) have been tested by an authorized institution such as TÜV SÜD, with priority being given to aspects of safety. In the meantime, the German GS-mark has been recognized as one of the crucial marks within product safety.

Features :

- Three-part telescopic lifter with galvanized steel sections
- TÜV/GS certified, certificate available
- CE certified complying with DIN EN ISO 12100-2, DIN 15560-27, certificate available
- 1-gear winch for easy lifting of the loads
- 5 mm steel rope
- Automatic braking system
- Safety-pins for mechanic locking
- Third safety device via massive block locking
- Four massive outriggers for highest stability
- Outriggers are firmly connected with the base, the finishing is velcro-protected
- Uneven grounds can be compensated via individually adjustable levelling braces
- Four auto-levelling, galvanized foot plates
- Truss lifter can be fixed via holes in the foot plates
- Easy transport via 100 mm swivel castors

Logistica

EAN / GTIN: 4026397277920

Peso : 76,45 kg

Lunghezza : 2.00 m

Larghezza : 0.47 m

Altezza : 0.55 m

Merci voluminose

- 4 swivel castors for vertical transport, 2 with brake
- 2 additional castors for horizontal transport
- Powder-coated base and galvanized sections for highest corrosion protection
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Regolabile in altezza

Dati tecnici :

Portata massima:	150 kg
Carico minimo:	25 kg
Norma:	DIN 15560-27, DIN EN ISO 12100-2
Altezza:	Maximum: 480 cm above 3 sections Minimum: 195 cm
Sistema di registrazione:	Ø 35mm
Fune d'acciaio:	Ø 5 mm
Tipo (treppiede generico):	Sollevatore a traversa
Materiale:	Acciaio, 2 mm
Dimensioni di trasporto:	195 cm x 55 cm x 42 cm
Superficie espositiva:	Ø 213 cm
Peso:	67,00 kg

Contenuto della confezione: