

ANTARI AF-14 IP Effect Fan

Weather-proof wind machine with DMX/RDM and timer, 4500 m³/h

Art.n.: 80208084

GTIN: 4710586557046



Prezzo di listino: 1902.81 €

incl. 19% IVA

Descrizione :

The Antari AF-14 is a high-velocity fan (4500 m³/h) engineered for professional applications, combining power, precision and long-term durability. Its IP-55 rated, splash-resistant construction makes it a reliable choice for demanding environments where moisture, dust or outdoor conditions are a concern - a major advantage for touring, stage productions and permanent installations.

Featuring a unique swirl-shaped front cover, the AF-14 maintains a focused airflow while reducing turbulence and noise. The specially designed aerodynamic blades deliver optimal air distribution with minimal sound, ensuring smooth and quiet performance ideal for stage, studio, and installation use.

Built with robust materials for consistent reliability, the AF-14 operates with a simple plug-and-run setup and comes with the AFC-1 control box for advanced control via DMX, W-DMX or wireless remote. Built for professionals, the control box features variable speed adjustment and a built-in timer function, allowing precise control over airflow duration and intensity.

Whether for fog dispersion or wind effects, the AF-14 provides efficient, quiet and stable airflow that meets the needs of professional environments.

Features :

- Adatto, tra l'altro, per l'uso con macchine per nebbia, neve e bolle di sapone
- Angolo di uscita dell'aria modificabile
- Timer regolabile con intervallo, durata e quantità di vento
- Può funzionare in modalità 1 CH DMX
- Controllabile via stand-alone; timer; DMX; RDM; radiocomando (opzionale); W-DMX by wireless solution (opzionale)

Logistica

EAN / GTIN: 4710586557046

Peso : 17,20 kg

Lunghezza : 0.53 m

Larghezza : 0.54 m

Altezza : 0.41 m

- Con Staffa di montaggio
- Per campi di applicazione come, ad esempio,: DJ mobili/Intrattenitori solisti
- Massima silenziosità

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	145 W
Grado di protezione:	IP55
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite IP T-Con (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Regime:	1650 Giri/min
Portata di aria massima:	4500 m³/h
Canali DMX:	1
Ingresso DMX:	1 x XLR (M) a 5 poli IP versione da incasso
Uscita DMX:	1 x XLR (F) a 5 poli IP versione da incasso
Attivazione:	Stand-alone; timer; DMX; RDM; radiocomando (opzionale); W-DMX by wireless solution (opzionale)
Colore della custodia:	Nero
Sistema di registrazione:	2x Staffa di montaggio
Peso:	14,55 kg
Classificazione del rumore:	Classe 1 (rumore molto leggero, adatto per ambienti sensibili al rumore)
Misure:	Lunghezza: 43,2 cm Larghezza: 65,6 cm Altezza: 62,3 cm
Misure:	Lunghezza: 26,6 cm Larghezza: 16,3 cm Altezza: 5,3 cm

Contenuto della confezione:

1 x Ventola
 1 x Controller
 1 x Cavo di rete/Cavo di alimentazione
 1 x Manuale d'uso
 2 x Staffa di montaggio
 2 x vite a testa zigrinata
 6 x Rondella