

EUROLITE LSD AIO Network control system

All-in-one network control system LED Show T9 for LED Soft Displays

Art.n.: 80503300

GTIN: 4026397390186



L'articolo non è più disponibile.

Features :

- Complete network control system including network interface and software LED show T9 on CD-ROM for controlling LED soft displays with a network-compatible computer
- Ideal control system for mobile use with notebooks with 1 Gbps NIC - requires no additional video card
- 1 network interface allows control of 128 x 128 pixels
- Serial connection of network interfaces possible for control of up to 1024 x 896 pixels
- 8 data signal outputs (each controls 128 x 16 pixels) for connection to LED display panels
- Ethernet input and output, LAN cable included
- System requirements: separate 1 Gbps NIC, Windows 2000/XP/Vista, >1.8 GHz CPU, >1 GB disk space
- Power supply via LED soft displays
- Software functions:
 - supports movies, flash, pictures, and live camera input
 - audio-driven flash animations
 - multiple screen output
 - automated effect parameters
 - up to 6 simultaneous
 - mix up to 3 layers using 18 different overlay
 - user-definable transitions and masks
 - scratch video
 - control playback speed and direction
 - file browser with clip information and preview
 - supports TheaterMode for ATI video cards
 - compatible to media software such as MADRIX

Logistica

EAN / GTIN: 4026397390186

Peso : 2,04 kg

Lunghezza : 0.33 m

Larghezza : 0.30 m

Altezza : 0.07 m

Dati tecnici :

Misure:	Larghezza: 16 cm Profondità: 4,8 cm Altezza: 13 cm
Peso:	1,84 kg
Power supply:	5 V DC via display
Signal input:	LAN, CAT5E
Signal link:	LAN, CAT5E
Signal output:	8 x 15-pin DIN jack
Serial connection:	max. 56 units
Resolution:	max. 1024 x 896 pixels
Dimensions (L x W x H):	160 x 130 x 48 mm