

OMNITRONIC MPZ-250.6P PA Mixing Amplifier

Art.n.: 80709732

Amplificatore di miscelazione ELA a 6 zone con lettore audio e telecomando IR, zone commutabili, zone commutabili, 250 W RM



Descrizione :

Enormous reliability with a maximum of flexibility

The Omnitronic MPZ-250.6P ELA mixer amplifier is your reliable partner for ELA sound reinforcement systems. Thanks to its 19" format, it is ideally suited for both mobile and permanent installations.

Outputs for ELA loudspeakers with 70 V and 100 V audio transformers or 4-16- Ohm loudspeakers leave nothing to be desired. In addition, you can also connect a device with line level (e.g. mixing console) to the line output. With 6 mixable inputs you are always flexible. Connect up to 3 microphones and 3 line level devices.

Control your ELA speakers conveniently via the 6 zone outputs of the MPZ-250.6P. They can be switched separately on the front panel. For you, this means the greatest possible adaptability when implementing your sound reinforcement concept.

The MPZ-250.6P also offers you an MP3 player with infrared remote control and blue backlit LCD display. It has both an SD card slot and a USB port. So you can spontaneously and flexibly play music titles from a storage medium of your choice.

Make yourself heard!

The microphone input at the front has an adjustable priority switch. It allows you to make important announcements with automatic, continuously adjustable level reduction of all signals. You can also use the gong to draw attention to your announcement.

Protective functions

A fan protects the interior of your MPZ-250.6P from overheating. In addition to a switch-on delay, it has protection circuits against overvoltage and short-circuits. In these cases, your loudspeakers are electrically isolated from the amplifier. This protects both the MPZ-250.6P and your speakers from damage.

Logistica

EAN / GTIN: 4026397503494

Peso : 12,90 kg

Lunghezza : 0.54 m

Larghezza : 0.49 m

Altezza : 0.18 m

Features :

- Comfortable control of PA speakers via 6-zone technology
- 6 PA zone outputs, independently switchable on the front panel
- Master PA output (70 V and 100 V)
- Output for low-impedance speakers (4-16 ohms)
- SD card slot and USB port
- Folder navigation and repeat functions (1, All)
- 2 rear microphone inputs (6.3 mm jack, unbal.)
- 1 front microphone input (combination XLR/6.3 mm jack, unbal.) with adjustable priority circuit
- All microphone inputs with separate level controls
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- Protection circuits with LED indication: over current, short circuit, turn-on delay
- Rack installation, brackets detachable
- Montaggio su rack (19") 48,3 cm 2 U
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via Telecomando IR

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	500,00 W
Potenza in uscita:	250 W RMS
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Intervallo di frequenza:	80 - 16000 Hz
Rapporto segnale-rumore:	>75 dB microfono >85 dB line
Distorsione armonica totale:	<0,5 % a 1 kHz
Raffreddamento:	Ventola
Impedenza:	ELA tecnica 100 V; 4-16 Ohm
Attivazione:	Telecomando IR
Audioplayer:	USB + SD
Uscita zona:	6 zone commutabili
Commutazione:	Class AB
Collegamenti:	Ingresso: microfono via 2 x Jack da 6,3 mm (non sim.) Ingresso: microfono via 1 x presa combinata XLR a 3 poli/jack da 6,35 mm (F) versione da incasso Ingresso: line via 3 x RCA stereo 0,3 V Uscita: Altoparlante via terminale a vite Uscita: rec. via 1 x RCA stereo
Equalizzatore:	Master: 1 x regolatore a 2 bande Mono
Formato musicale:	MP3
Numero di file:	Massimo 999
Supporti di memorizzazione appropriati:	Periferica USB/Schede SD max. 32GB (FAT 32)
Struttura della custodia:	Montaggio su rack (19") 48,3 cm 2 U
Misure:	Larghezza: 48,3 cm Profondità: 38,5 cm

Altezza: 8,9 cm

Peso: 11,25 kg

Pila: Pila a bottone 3,0 V CR2025 litio-manganese montato

Contenuto della confezione:

1 x Manuale d'uso
1 x Amplificatori
1 x telecomando
1 x Pila